

FLIR SCOUT TS-X SERIES

Handheld Thermal Night VisionCamera

THE ULTIMATE PACKAGE: PALM-SIZED POWERFUL THERMAL IMAGING

When you want a thermal camera that's easy to pack, easy to use and delivers a high-quality thermal image that you can rely on, the FLIR TS-X Series of thermal night vision cameras is your ideal choice. Multiple lens and thermal detector options allow you to customize the right camera for you. Tracking game in a heavily forested area? TS-X lets you see in the dark and through light foliage and camouflage. Monitoring a herd? Perhaps the TS-XR is your best option, so you can observe from more than a half-mile away.

KEY FEATURES OF THE SCOUT TS-SERIES INCLUDE:

Two Resolution/Detector Options: Choose from a crisp 240×180 resolution image or the even more astonishing 320×240 resolution.

Multiple Lens Options: 19 mm lens with a 24° field of view; long-range 65 mm lens with a 7° field of view.

 $\textbf{Easy Operation:} \ \ \textbf{Engage power, recording,* zooming,* brightness and polarity at the push of a button.}$

Shuttered Eyepiece: Seals light in the viewfinder so you won't alert animals or other targets to your location.

SD Card Slot: Store still images and video on a removable SD card.*

USB2 Connection: Permits rapid transfer of still images and video to a PC.*

*Pro models only







	TO 1/	T0.1/10	TO 1/10	T0.1/0.0
SYSTEM	TS-X	TS-X Pro	TS-XR	TS-XR Pro
Resolution	240 x 180		320 x 240	
Field of View	24° x 18°/12° x 9°		24° x 18°/12° x 9°	
Size (L x W x H)	9.36" x 3.33" x 2.62"		9.36" x 3.33" x 2.62"	
Weight (w/o lens)	1.59 lb		1.59 lb	
Operating Temp.	32°F to 122°F (0°C to 50°C)		-4°F to 140°F (-20°C to 60°C)	
IMAGE PRESENTATION				
Polarity	White Hot, Black Hot, InstAlert™			
Freeze Frame	Not avaliable with Pro models			
Video Output (9 Hz refresh rate)	NTSC or PAL composite video			
Video/Still Image Storage, SD/SDHC Card-enabled (up to 16Gb)	Pro models only			
COMMON FEATURES				
Startup	2 seconds			
E-Zoom	2x avaliable on all models except TS24			
Battery	4 AA NiMH Batteries (included) or Li-lon or Alkaline AA			
Rating	IP-67			
INCLUDED ACCESSORIES				
TS24/TS32/TS32r	Basic Kit (neck lanyard, video cable, operator's manual)			
TS24Pro/TS32Pro/TS32r Pro	Basic Kit, tactical bag, USB cable, SD card			
OPTIONAL ACCESSORIES		_	_	
TS24/TS32/TS32r	Tactical bag			
TS24Pro/TS32Pro	2x optical extender			
LENSES (Purchased Separately)	QD35	QD65	QD100	QD35
Size	Ht 2.2"	Ht 3.3"	Ht 4.6"	Ht 2.2"
	Dia - 3.1" Ø	Dia - 3.1" Ø	Dia - 3.1" Ø	Dia - 3.1" Ø
FOV (320 x 240)	13° × 10°	7° × 5°	5° × 3°	18° × 13°
E-Zoom FOV (Resolution):				
2x	6.5° × 5° (160 × 120)	3.5° × 2.5° (160 × 120)	2.5° × 1.5° (160 × 120)	9° × 6.5° (320 × 240)
4x	N/A	N/A	N/A	4.25° × 3.25° (160 × 120)
LENS PACKAGE INCLUDES:	QD35, QD65 or QD100 Lens (as selected at purchase), Lens Cap, Lens Cover, Lens Cloth			
RANGE PERFORMANCE				
Detect Man (1.8 m × 0.5 m)	~850 yds	~1,400 yds	~1.2 mi	~1,200 yds
Detect Vehicle (4 m × 1.5 m)	~1.3 mi	~2.4 mi	~3.2 mi	~1.5 mi
Country of Origin	U.S.A.			
			-11-1-1-1 1	

Actual range may vary depending on camera setup, focus adjustment (if available), environmental conditions (i.e., humidity, rain, snow, fog, etc.), user experience, and display method.

Visit www.FLIR.com/scout for more information

AMERICAS

Billerica 25 Esquire Road N. Billerica, MA 01862 USA 1-866-404-5627

São Paulo Av. Antonio Bardella, 320 Sorocaba, SP 18052-852 Brasil +55 15 3238-8075

ASIA

Shanghai K301-302, No 26 Lane 168, Daduhe Road Putuo District, Shanghai 200062 P.R.China +86-21-5169-7628

EUROPE

Luxemburgstraat 2 2321 Meer Belgium +32 3665-5100

CORPORATE HEADQUARTERS

Portland 27700 SE Parkway Ave. Wilsonville, OR 97070 USA 877-773-3547

Always consult lederal, state, and local laws governing lishing, bunding, and shooting sports prior to the use of this thermal/infrared night vision camera to ensure full compliance with all appropriate regulations governing sportsman uses. Packe and local laws vary, so regularly consult those specific to the region of use/activity of interest. Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US hav is prohibited © 2015 FUIR Systems, Inc. Specifications are subject to change without notice. Visit filt cam for the most up-to-date specifications, 100615

