

# HOLOSUN

PRECISION PERFORMANCE INNOVATION



## ELITE-2018



[WWW.HOLOSUN.COM](http://WWW.HOLOSUN.COM)

**HOLOSUN TECHNOLOGIES INC**



# Company Introduction

Holosun Technologies, located in Walnut California, was established in 2013. Holosun is committed to creating innovative optics and laser that benefit a broad range of shooting, hunting, law enforcement and military needs. We provide military grade products without military grade price.

## TABLE OF CONTENTS

1. Holosun Elite Series
2. Open Reflex Sight
3. Mirco Reflex Sight
4. Tube Reflex Sight
5. Laser & Illuminator
6. Product Specification



Holosun  
HSS15CU CIRCLE DOT #1010100034

Holosun

# Elite Series

Holosun is proud to announce the launch of our new "Elite" product series. With new innovations, features and technologies from a brand you've come to trust.

**Green LED Emitter:** Holosun is the first to introduce a revolutionary Green LED emitter featuring: 1. Extremely High Visibility; 2. Multiple Reticle System™; 3. Higher efficiency than red LED emitter.

**Titanium Body:** Holosun is the first to introduce an entire titanium housing. Titanium is stronger, and more resistant to corrosion than aluminum.


**Advanced Solar Fail Safe:** In solar mode, the solar cell/light sensor, powers the LED reticle and can also draw power from the battery if light source is insufficient.

**Shake Awake™:** Holosun's Shake Awake™ technology allows the optics to power down to "sleep mode" after a preset time of inactivity and to automatically power on with the slightest movement.

# HS512T ELITE

## Open Reflex Sight

### HS512T Elite



### Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 0.91\*1.2 Inches

### Features

- Up to 50,000 Hour Battery Life
- Reticle Color: Green or Red
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot; 2 MOA Dot; 65 MOA Circle
- Solar Fail Safe™
- Shake Awake™ - Motion On With Last Setting Recall.
- Entire Titanium Body
- Parallax Free & Unlimited Eye Relief






# HS508T ELITE

## Open Reflex Sight

HS508T Elite



### Features

- Up to 100,000 Hour Battery Life
- Reticle Color: Green or Red
- Multiple Reticle System™: 32 MOA Circle & 2 MOA Dot; 2 MOA Dot; 32 MOA Circle
- Solar Fail Safe™
- Shake Awake™ - Motion On With Last Setting Recall
- Entire Titanium Body
- Parallax Free & Unlimited Eye Relief

### Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 0.63 \* 0.91 Inches

2018-ELITE HOLOSUN PRODUCT   
www.holosun.com

# HS510C ELITE

## Open Reflex Sight



HS510C Elite



Green Circle Dot

### Features

- Up to 50,000 Hour Battery Life
- Green LED Emitter
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot; 2 MOA Dot; 65 MOA Circle
- Solar Fail Safe™
- Shake Awake™ - Motion On With Last Setting Recall
- Titanium Hood
- Parallax Free & Unlimited Eye Relief

### Specifications


- IP67 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 0.91\*1.2 Inches



# HS407/507C ELITE


## Open Reflex Sight

### HS407C Elite



Green Dot

### HS507C Elite



Green Circle Dot

## Features

- Up to 100,000 Hour Battery Life
- Green LED Emitter
- 2 MOA Dot only (407); Multiple Reticle System™ (507)
- Solar Fail Safe™
- Shake Awake™ - Motion On With Last Setting Recall.
- Parallax Free & Unlimited Eye Relief
- CNC Milled 7075 Aluminum

## Specifications

- IP67ertified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 0.63 \* 0.91 Inches



2018-ELITE HOLOSUN PRODUCT  
www.holosun.com

6



# HS515GT/CT/GTC ELITE

## Mirco Reflex Sight



**HS515GT Elite**



**HS515CT Elite**

### Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 22 mm Diameter


### Features

- Up to 50,000 Hour Battery Life
- Reticle Color: Green or Red
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot; 2 MOA Dot
- Solar Fail Safe™ (S15CT)
- Shake Awake™ - Motion On With Last Setting Recall
- Entire Titanium Body
- Parallax Free & Unlimited Eye Relief



**HS515CT Elite**

**HS515GT Elite**





## Features

- Up to 50,000 Hour Battery Life
- Green LED Emitter
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot
- Solar Fail Safe™ (515CM)
- Shake Awake™ - Motion On With Last Setting Recall.
- CNC Milled 7075 Aluminum
- Parallax Free & Unlimited Eye Relief

# HS515GM/CM ELITE

## Mirco Reflex Sight

## Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 22 mm Diameter



HS515CM Elite



HS515GM Elite



HS515GM Elite

HS515CM Elite



Green Circle Dot

# HS503GU/CU ELITE

## Mirco Reflex Sight

HS503GU Elite

HS503CU Elite



HS503CU Elite



HS503GU Elite

### Features

- Up to 50,000 Hour Battery Life
- Green LED Emitter
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot; 2 MOA Dot
- Solar Fail Safe™ (503CU)
- Shake Awake™ - Motion On With Last Setting Recall.
- Parallax Free & Unlimited Eye Relief

### Specifications

- IP67 Certified Waterproof
- 1/2 MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 22 mm Diameter



# HS403 SERIES ELITE

## Mirco Reflex Sight

### Features

- Up to 50,000 Hour Battery Life
- Green LED Emitter
- 2 MOA Dot Reticle
- Solar Fail Safe™ (403C)
- Shake Awake™ - Motion On With Last Setting Recall.
- Parallax Free & Unlimited Eye Relief

### Specifications

- IP67 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 22 mm Diameter

HS403C Elite


HS403B Elite

HS403GL Elite

HS403B Elite

HS403C Elite

HS403GL Elite






# HS530G/C/GC ELITE

## Tube Reflex Sight

HS530C Elite

HS530G Elite

HS530GC Elite



**HS530C Elite**



**HS530G Elite**



**HS530GC Elite**

### Features

- Up to 50,000 Hour Battery Life
- Reticle Color: Green or Red
- Multiple Reticle System™: 65 MOA Circle & 2 MOA Dot; 2 MOA Dot;
- Solar Fail Safe™
- Shake Awake™ - Motion On With Last Setting Recall.
- Entire Titanium Body
- Parallax Free & Unlimited Eye Relief

### Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 30 mm Diameter





## Features

- Up to 50,000 Hour Battery Life
- Green LED Emitter
- 2 MOA Dot Reticle (406); Multiple Reticle System (506)
- Shake Awake™ - Motion On With Last Setting Recall.
- Parallax Free & Unlimited Eye Relief

# HS406A/506 ELITE

## Tube Reflex Sight



## Specifications

- IP67 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 50 MOA
- 10 Daylight and 2 Night Vision Compatible Brightness Setting
- Window Size: 30 mm Diameter



**HS406A Elite**



Green Dot

**HS506 Elite**



Green Circle Dot

2018-ELITE **HOLOSUN PRODUCT**

[www.holosun.com](http://www.holosun.com)

12

# LS420 ELITE

## Laser & Illuminator

### Features


- Coaxial Laser Mechanism
- Visible & IR Laser Pointer
- IR Laser & White LED Illuminator
- Rear-end Adjustable Focusing Knob
- Multifunctional Mode Selector
- Entire Titanium Body

### Specifications

- IPX8 Certified Waterproof
- ½ MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 60 MOA
- Two CR123A/One 18650 Battery



### LS420 Elite+Reflex Sight



LS420R Elite+



LS420G Elite+



LS420R Elite

LS420G Elite



## Specifications

- IPX8 Certified Waterproof
- 1/2 MOA Windage & Elevation Adjustment Per Click
- Travel Range +/- 60 MOA
- One CR123A

# LS321/221 ELITE

## Laser & Illuminator



**LS221 Elite**



**LS321 Elite**

## Features

- Coaxial Laser Mechanism
- Visible & IR Laser Pointer
- IR Laser Illuminator (321)
- Rear-end Adjustable Focusing Knob
- Multifunctional Mode Selector
- Entire Titanium Body



**LS321R Elite+**

**LS321G Elite+**



**LS221R Elite+**

**LS221G Elite+**

## LS321 Elite+ Reflex Sight



**LS321R Elite+**



**LS321G Elite+**




# LS117/322 ELITE

## Laser & Illuminator



LS117 Elite

- LS117R Elite
- LS117G Elite
- LS117IR Elite



## Features (LS322 Elite)

- Visible & IR Laser Pointer
- 600 Lumens Flashlight
- Entire Titanium Body
- Quick Release Mount



LS322 Elite



LS322 Elite

## Specifications (LS117/322 Elite)

- IPX8 Certified Waterproof
- 1/2 MOA Windage & Elevation Adjustment Per Click (LS117 Elite)
- Travel Range +/- 60 MOA



LASER AND FLASHLIGHT	LS420 Elite	LS321 Elite	LS221 Elite	LS117 Elite	LS322 Elite
<b>FUNCTIONS</b>					
Green Laser Pointer	▲	▲	▲	▲	●
Red Laser Pointer	●	●	●	●	○
IR Laser Pointer	○	○	○	○	○
IR Laser Illuminator	○	○	○	○	○
Flashlight	●	○	○	○	●
<b>OPTICAL DATA</b>					
Green or Red Laser Output Power (mw)	5	5	5	5	5
Green or Red Laser Class	IIIa	IIIa	IIIa	IIIa	IIIa
IR Pointer or Illuminator Output Power (mw)	0.7	0.7	0.7	0.7	0.7
IR Pointer or Illuminator Class	2M	2M	2M	2M	2M
Green Laser Wavelength (nm)	520	520	520	520	520
Red Laser Wavelength (nm)	635	635	635	635	635
IR Laser Wavelength (nm)	830	830	830	830	830
Flashlight Output Power (lum)	600	N/A	N/A	N/A	600
<b>ELECTRONIC DATA</b>					
Battery	CR123A/18650	CR123A	CR123A	CR123A	CR123A
Battery Life					
<b>MECHANICAL DATA</b>					
Housing Material	Titanium	Titanium	Titanium	Titanium	Titanium
Surface Finish	Titanium Finish	Titanium Finish	Titanium Finish	Titanium Finish	Titanium Finish
Housing Color	Black	Black	Black	Black	Black
Laser Adjustment per Click	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA
Laser W&E Travel Range	±60 MOA	±60 MOA	±60 MOA	±60 MOA	±60 MOA
Storage Temperature	-40°F~149°F	-40°F~149°F	-40°F~149°F	-40°F~149°F	-40°F~149°F
Working Temperature	-40°F~123.8°F	-40°F~123.8°F	-40°F~123.8°F	-40°F~123.8°F	-40°F~123.8°F
Submersion	IPX8(5M)	IPX8(5M)	IPX8(5M)	IPX8(5M)	IP67
Vibration	1000G	1000G	1000G	1000G	1000G
<b>PHYSICAL DATA</b>					
Dimension (in)	3.66×3.07×1.46	3.7×2.24×1.46	3.43×1.77×1.34	3.43×1.77×1.34	3.35×1.46×1.61
Weight (oz)	10.94	9.52	6.88	6.7	4.23

NOTE: ● Has this feature ○ Does not have this feature ▲ Choose one of these features at purchase

Reflex Sight	Micro Sight							
	HS403B Elite	HS403C Elite	HS403GL Elite	503CU Elite	HS503GU Elite	HS515CM Elite	HS515GM Elite	HS515CT Elite
<b>FUNCTIONS</b>								
Selectable Reticle	○	○	○	●	●	●	●	●
Solar Power	○	●	○	●	○	●	○	●
Shake Awake Technology	●	●	●	●	●	●	●	●
Memory	●	●	●	●	●	●	●	●
<b>OPTICAL DATA</b>								
Light Source (Wavelength)	LED(540nm)	LED(540nm)	LED(540nm)	LED(540nm)	LED(540nm)	LED(540nm)	LED(540nm)	LED(540/650nm)
Reticle	2 MOA Dot	2 MOA Dot	2 MOA Dot	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle
No Parallax	●	●	●	●	●	●	●	●
Unlimited Eye Relief	●	●	●	●	●	●	●	●
Magnification	1x	1x	1x	1x	1x	1x	1x	1x
Multi-Coatings	●	●	●	●	●	●	●	●
Laser								
<b>ELECTRONIC DATA</b>								
Battery	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032
Battery Life	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours
Brightness Setting	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible	10 Dlt & 2NV Compatible
<b>MECHANICAL DATA</b>								
Housing Material	6061 T6 Aluminum	6061 T6 Aluminum	6061 T6 Aluminum	6061 T6 Aluminum	6061 T6 Aluminum	7075 T6 Aluminum	7075 T6 Aluminum	Titanium
Surface Finish	MAO	MAO	MAO	MAO	MAO	Hard Anodized	Hard Anodized	
Housing Color	Black	Black	Black	Black	Black	Black	Black	Black
Adjustment per Click	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA
W&E Travel Range	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA
Storage Temperature	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F
Working Temperature	-22°F~140°F	-22°F~140°F	-22°F~140°F	-22°F~140°F	-22°F~140°F	-40°F~140°F	-40°F~140°F	-40°F~140°F
Submersion	IP67	IP67	IP67	IP67	IP67	IPX8	IPX8	IPX8
Vibration	1000G	1000G	1000G	1000G	1000G	1000G	1000G	1000G
<b>PHYSICAL DATA</b>								
Window Size (in)	20mm Diameter	20mm Diameter	20mm Diameter	20mm Diameter	20mm Diameter	20mm Diameter	20mm Diameter	20mm Diameter
Dimension (in)	2.45×1.43×1.6	2.45×1.43×1.6	2.4×1.43×1.43	2.6×1.43×1.6	2.6×1.43×1.43	2.75×1.43×1.62	2.73×1.53×1.61	2.67×1.45×1.6
Weight (oz)	2.82	2.82	2.72	3	2.93	3.53	3.74	4.06
Central Height (in)	0.74	0.74	0.571	0.74	0.571	0.772	0.772	0.772

# Reflex Sight

Tube Sight					Open Reflex Sight				
HS515GT Elite	HS406A Elite	HS506 Elite	HS530C Elite	HS530G Elite	HS407C Elite	HS507C Elite	HS508T Elite	HS510C Elite	HS512T Elite
●	○	●	●	●	●	●	●	●	●
○	○	○	●	○	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●
LED(540/650nm)	LED(540nm)	LED(540nm)	LED(540/650nm)	LED(540/650nm)	LED(540nm)	LED(540nm)	LED(540/650nm)	LED(540nm)	LED(540/650nm)
2 MOA Dot & 65MOA Circle	2 MOA Dot	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot	2 MOA Dot & 32MOA Circle	2 MOA Dot & 32MOA Circle	2 MOA Dot & 65MOA Circle	2 MOA Dot & 65MOA Circle
●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●
1x	1x	1x	1x	1x	1x	1x	1x	1x	1x
●	●	●	●	●	●	●	●	●	●
CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032	CR2032
50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours	100,000 Hours	100,000 Hours	100,000 Hours	50,000 Hours	50,000 Hours
10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible	10 DLt & 2NV Compatible
Titanium	6061 T6 Aluminum	6061 T6 Aluminum	Titanium	Titanium	6061 T6 Aluminum	6061 T6 Aluminum	Titanium	Aluminum & Titanium Hood	Aluminum & Titanium Hood
	MAO	MAO			MAO	MAO		MAO	MAO
Black	Black	Black	Black	Black	Black	Black	Black	Black	Black
0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA	0.5 MOA
±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA	±50 MOA
-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F	-40°F~158°F
-40°F~140°F	-40°F~140°F	-40°F~140°F	-40°F~140°F	-40°F~140°F	-22°F~140°F	-22°F~140°F	-40°F~140°F	-22°F~140°F	-22°F~140°F
IPX8	IP67	IP67	IPX8	IPX8	IP67	IP67	IPX8	IP67	IP67
1000G	1000G	1000G	1000G	1000G	5000G	5000G	1000G	1000G	1000G
20mm Diameter	30mm Diameter	30mm Diameter	30mm Diameter	30mm Diameter	0.63×0.91	0.63×0.91	0.63×0.91	0.91×1.26	0.91×1.26
2.67×1.51×1.6	5.2×1.9×2	5.2×1.9×2	3.22×1.65×1.87	3.22×1.9×1.77	1.78×1.15×1.15	1.78×1.15×1.15	1.78×1.15×1.15	3.3×1.68×1.78	3.35×1.63×1.7
4.33	6.17	6.17	6.77	6.56	1.34	1.34	1.76	4.94	6.77
0.772	0.945	0.945	0.957	0.839	0.622	0.622	0.622	1.04	26.3



The entire family of products is available to see at [www.holosun.com](http://www.holosun.com). This printed material is for information purpose only and does not constitute any binding obligation or agreement by Holosun.

**HOLOSUN TECHNOLOGIES INC**  
[WWW.HOLOSUN.COM](http://WWW.HOLOSUN.COM)

