

RETICLES

60


NIGHT VISION

BINOCULARS

RIFLESCOPES

66





ALL-ROUNDERS MADE IN GERMANY



OUR RIFLESCOPES FOR HUNTING



FEATURES

- 94 % light transmission¹ thanks to M*plus coating
- Fast Target Acquisition FTA: improved viewing comfort through enlarged ocular
- Glass Fiber Point: finely dimmable glass fiber reticle suitable for day and night use
- Automatic deactivation of the red dot via position sensor
- Extra low adjustment towers for a better overview
- Comfort Service 30-year warranty (after registration)
- Made in Germany

 $^{\mathrm{1}}$ In conformance with spectral transmissions according to DIN ISO 14490-5




ALL-ROUNDERS

FAST ON TARGET – BY DAY AND BY NIGHT!

A scope for every hunting application: From a driven hunt to sitting in a hide until the last light of the day – the MINOX riflescope line is fully tailored to the demands of any hunting situation. Our all-rounders are true workhorses and have all the functionality you would not want to miss out on when out in your district. What more do you want?



MADE IN GERMANY



- **1** | Improved viewing comfort with Fast Target Acquisition (FTA)
- **2** | Extra low adjustment towers for a better overview
- **3** | Automatic deactivation of the red dot via position sensor i.e. after 2 hours
- **4** | Glass Fiber Point finely dimmable glass fiber reticle



INCLUDING BEST PROTECTION FOR YOUR SCOPE

The Tenebraex flip-up covers are included in the delivery – for a reliable protection of objective and eyepiece with every use.

Tenebræx

Fig. shows original size


ALL-ROUNDERS

MADE IN GERMANY

BRIGHT & VERSATILE

The MINOX riflescope line provides you with an outstanding transmission of up to 94 %*. For hunting at any time of the day, the bright glass fiber reticle can be finely dimmed. The Fast Target Acquisition (FTA) greatly improves your eye relief to get you quickly and easily on target. The extra low adjustment towers give you an optimal overview in every situation. And the illuminated reticle with a position sensor has an automatic switch-off function.

Hunt your moment – with your MINOX scope!



94%*

A maximum transmission of up to 94 %* provides outstanding performance in all lighting conditions. A brilliant image even in bright sunlight and excellent contrast allow for proper aiming from dusk till dawn.

 * in conformance with spectral transmissions according to DIN ISO 14490-5



1-5x24



2-10x50



3-15x56



INTO THE LAST LIGHT


THE MINOX RIFLESCOPES – OUTSTANDING TRANSMISSION


The excellent transmission of MINOX riflescopes is the direct result of a sophisticated lens coating concept.

With a maximum transmission of up to 94%* and a cleverly balanced transmission curve throughout the entire visible light spectrum, our riflescopes achieve outstanding performance in all lighting conditions. A brilliant and detailed image in the bright sunlight as well as an excellent contrast during twilight allow for accurate targeting from the early morning hours into the last light of day – for unforgettable hunting experiences on driven hunts, while stalking or hunting from a hide.

Depending on the time of the day and the respective light conditions, long-wave red or short-wave blue light within the visible spectrum are more dominant. The sensitivity of the human eye is particularly receptive to the so-called v-lambda curve within the middle of the visible wavelength spectrum. Taking these physical principles into consideration, the multi-layer coatings used on the lenses have been designed to guarantee an optimal and consistent visual impression even when light conditions are poor.

^{*} in conformance with spectral transmissions according to DIN ISO 14490-5





FTA - FAST TARGET ACQUISITION

The perfect interplay of scope, hunter and rifle are paramount for a successful hunt. When getting on target, the image produced by the riflescope is a decisive factor. It is exactly here, where the Fast Target Acquisition (FTA) plays out its strengths: Spending a lot of time positioning your eye behind your riflescope is now a thing of the past.

And this is how it works: The optical design of those MINOX riflescopes featuring FTA has reduced vignetting to an absolute minimum. This not only ensures an exceptionally bright and sharp image all the way to the outer edges of the field of view, but also increases the size of the exit pupil. This allows you to quickly align your eye with your riflescope and inside the exit pupil. The result: The FTA gets you fast on target for a safe and accurate shot.

FUNCTIONAL PRINCIPLE


WITH FTA

WITHOUT FTA

PRECISE & EFFICIENT

GLASS FIBER RETICLE

The innovative glass fiber reticle in the second focal plane impresses with a precise, circular illuminated dot, which you can adjust perfectly to any hunting situation during the day or at night.






Partially grounded fiber end to project a fine point of light

FUNCTIONAL PRINCIPLE ILLUMINATED RETICLE



Enlarged view of the illuminated glass fiber at the reticle center





Functional principle of loss-free light conduction through the glass fiber

AUTOMATIC DEACTIVATION

When putting your rifle aside, the innovative glass fiber reticle automatically switches off thanks to its integrated position sensors. This significantly increases battery life. Should the battery become empty, the battery compartment contains a second battery, which can be changed on the spot without loss of time.

In order to avoid inadvertent deactivation of the illumination, the sensors only react when the scope is moved by more than 75° to an upright position and 45° sideways.





PRO



OUR RIFLESCOPES FOR AMBITIOUS HUNTERS



FEATURES


- Rugged construction for highest shooting stability and shot repetitions
- 34 mm tube with thick walls made from a single piece of aircraft-grade aluminum
- M* multi-coating on the optical elements provides excellent light transmission, contrast and color rendition
- Generous 90 mm eye relief provides safety even for use with high calibers
- Practical design of operational elements: Quick and reliable adjustments even with gloves and in low light conditions
- Locking diopter adjustment ring to avoid accidental alterations; equipped with an adapter ring for use with robust protective caps
- Select between four practice-oriented reticles for any application
- Reticle illumination with automatic deactivation after 3 hours
- Waterproof according to IPX7 and protected against internal fogging
- Comfort Service 30-year warranty (after registration)



PRECISE UNDER ALL CONDITIONS

Several targets at various distances, poor visibility in adverse weather – hitting the target at long distances is often accompanied by tough conditions. How good it is, that MINOX developed the ZP series just for this purpose – offering you mechanical precision, optical quality and robust construction at the highest possible level.





- **1** | 5x magnification range for utmost flexibility
- **2** | 28 mrad Double Turn (DT) elevation adjustment with zero stop and indicator for the second turn
- **3** | Reticle in the first focal plane with finely dimmable illumination
- 4 | Parallax compensation from 50 m to infinity with 180° rotation angle

18 | MINOX hunting product range 2020 MINOX hunting product range 2020 | 1

PRO



RUGGED & POWERFUL

The MINOX ZP riflescope series has everything an ambitious marksman shouldn't be without: owing to complex optical design and the use of special types of glass, the unobstructed view provides you with a very large field of vision with an outstanding image quality all the way out to the edges of your image. The M* multi-coating offers excellent light transmission, contrast and color fidelity. A generous eye relief of 90 mm ensures maximum safety even when used with strong calibers.


Even the operating elements were designed with practical implementation in mind – adjustments can be easily made even when wearing gloves and in poor lighting conditions. Sophisticated and practice-oriented reticles at the first focal plane, and reticle illumination with automatic deactivation should of course not be missing from this high-performance package.





ZP5 5-25x56




ZP5 3-15x50










*Only available for ZP5 5-25x56



LONG-RANGE



OUR RIFLESCOPE FOR LONG DISTANCES



FEATURES

- Precise mechanics and rugged construction for highest shooting stability and shot repetitions
- Very large field of view and highest image quality, even at the edges owing to complex optical design and use of special types of glass
- M* multi-coating on the optical elements provides excellent light transmission, contrast and color rendition
- Generous 90 mm eye relief provides safety even for use with high calibers
- A brilliant image in the bright sunlight as well as an excellent contrast in the last light
- Ingeniously designed, practice-oriented long-range reticle at the first focal plane – for long distances
- Waterproof according to IPX7 and protected against internal fogging
- Comfort Service 30-year warranty (after registration)




LONG-RANGE

TARGET OPTICS FOR HIGHEST DEMANDS

Created for long distances. Created for difficult conditions. Created for you.

Our riflescope for long distances offers you mechanical precision, optical quality and robust construction at the highest level. A sophisticated and practice-oriented reticle at the first focal plane for every application should of course not be missing here.

Are you looking for a challenge under extreme conditions? Then the MINOX long-range riflescope is your choice!



IN GERMANY





INCLUDING BEST PROTECTION FOR YOUR SCOPE

The Tenebraex flip-up covers are included in the delivery – for a reliable protection of objective and eyepiece with every use.

Tenebræx

- **1** | 5x magnification range for utmost flexibility
- **2** | 28 mrad Double Turn (DT) elevation adjustment with zero stop and indicator for the second turn
- **3** | Ingeniously desinged long-range reticle in the first focal plane with finely dimmable illumination
- **4** | Parallax compensation from 50 m to infinity with 180° rotation angle

FAST CONFIDENT ROBUST 26 | MINOX hunting product range 202

FOR HUNTING ON THE MOVE

RED DOT SIGHT RV1


Are you in your element when on a driven hunt for wild boar? Then we would like to introduce you to your perfect companion: The MINOX RV 1 – our compact, enclosed red dot sight with 1x magnification. Its clear, fine 2 MOA red dot gives you a full overview and the greatest possible certainty when hunting at short distances. This allows you to aim at your target faster and with both eyes open without a defined eye distance. Use your speed with the RV 1!




FEATURES

- Very fine 2 MOA red dot for a fast target acquisition
- 11 brightness levels (3 NV optimized levels)
- Compact, robust and light construction
- Includes removable Weaver/Picatinny mount
- Up to 50,000 hours battery life
- Waterproof according to IPX7







SUPERIOR OPTICS FOR HUNTING

MADE

X-HD





FEATURES

- HD glass for high contrast and excellent detail recognition
- Very bright image even in poor visibility
- Large field of view (136 m at 1,000 m with the X-HD 8x44)
- Robust for rugged use
- Ergonomic handling with open bridge
- Comfort Service 30-year warranty (after registration)
- Made in Germany



OUR BEST FOR YOUR HUNT

X-HD

See more and identify your game faster – even in poor lighting conditions and at greater distances? No problem with the MINOX X-HD binoculars: the exclusive HD glass ensures high contrast and excellent detail recognition. Their high transmission enables a bright image when the last light is fading and in dark conditions. Not only that, you can benefit from the MINOX Comfort Service, which gives you a full 30-year warranty after registering your product. All binoculars in the X-HD series are superior optics – Made in Germany.



X-HD 8x44




X-HD 10x44



X-HD 8x56



32 | MINOX hunting product range 2020 MINOX hunting product range 2020



NATURE IS YOUR HUNTING GROUND

X-active





FEATURES

- M* multi-coating for an even brighter image
- Neutral color rendition and high contrast
- Large field of view (140 m at 1,000 m with the X-active 8x33)
- Versatile applications thanks to four different objective diameters
- Ergonomic handling with open bridge
- Comfort Service 30-year warranty (after registration)



OUR ALL-ROUNDERS FOR ANY SITUATION

X-active

With just one glance, you're right in the middle of the action: The MINOX X-active binocular series brings you closer to the game in your hunting grounds – thanks to 8x or 10x magnification and up to 140 m field of view. These powerful all-round talents offer you very good optical performance with neutral color rendition and high contrast, even in the last fading light or at dawn. The open Comfort Bridge provides a convenient operation and safe identification of game, even with one hand – an invaluable advantage when stalking, inspecting your hunting grounds or while sitting in your hide. Discover your new all-round binoculars for hunting now – with a 30-year warranty (after registering your binoculars at minox.com).



X-active 8x25 | 10x25



X-active 8x33 | 10x33



X-active 8x44 | 10x44



X-active 8x56





- **1** | Turnable eyecups: ideal for eyeglass wearers
- **2** | Neutral color rendition and high contrast
- **3** | Open Comfort Bridge for ergonomic handling
- **4** | Versatile applications thanks to four different objective diameters
- **5** | Waterproof according to IPX 7
- **6** | High detail recognition and large field of view



WHEN EVERY DETAIL COUNTS!

X-lite



FEATURES

- Neutral color rendition
- Turnable eyecups: ideal for eyeglass wearers
- Waterproof according to IPX7 and protected against internal fogging



OUR DEPENDABLES – FOR NEWCOMERS

X-lite

Stalking, sitting, inspecting – the MINOX X-lite binoculars are always at your side when the next adventure is around the corner. With their 8x or 10x magnification, they let you see details even at greater distances to help you positively identify your game. Their neutral color rendition and high contrast offer you very good imaging performance. Thanks to the robust housing, the X-lite series is also well protected against outside influences. A nitrogen filling prevents fogging from the inside. Discover your introduction to MINOX hunting optics - with binoculars from the X-lite series!



X-lite 8x26 | 10x26



X-lite 8x34 | 10x34




X-lite 8x42 | 10x42



X-lite 8x56



40 | MINOX hunting product range 2020 MINOX hunting product range 2020



OUR ROBUST ONE

BE INSTANTLY AWARE. BE CLOSER.

7.5x44 RAPID



FEATURES

- Single ocular focussing for an especially fast identification of objects at a distance of approximately 20 m no manual focussing necessary
- Innovative rubber wiper lips more effectively prevent the peneration of moisture and dirt
- Extremely robust metal twist-and-pull rotating eyecups
- 7.5x magnification for a steady image and wide field of view
- Comfort Bridge for secure one-handed use
- Light polycarbonate housing
- Waterproof and protected against internal fogging
- Comfort Service 30-year warranty (after registration)





RICH DETAILS COMPACTLY PACKED

MD 60 ZR / MD 80 ZR

SPOTTING SCOPE TECHNOLOGY REDEFINED



- Brilliant image
- M* multi-coating for increased light transmission
- Magnification: 12-40 x (MD 60 ZR), 20-60 x (MD 80 ZR)
- Robust, shock-resistant metal housing
- Waterproof according to IPX7 and protected against internal fogging
- Comfort Service 30-year warranty (after registration)

LEARN MORE ONLINE



POCKET-SIZED OPTICAL PERFORMANCE

MD 50 W

THE HANDY ALL-ROUND SPOTTING SCOPE



- High detail resolution and contrast
- M* multi-coating for increased light transmission
- 16x to 30x magnification
- Angled view
- Turnable tripod mount
- Waterproof according to IPX7 and protected against internal fogging
- Low weight
- Comfort Service 30-year warranty (after registration)

LEARN MORE ONLINE



YOUR NIGHT VISION DEVICE. YOUR MINOX.

OUR NIGHT VISION DEVICES FOR HUNTING

From dusk until deep into the night. Here, not only do your eyes reach their limits, but even high-performance binoculars. This is exactly where our night vision devices offer the decisive advantage: equipped with the latest technology, they clearly reveal those objects that would otherwise remain hidden from you as an observer. Whether on nocturnal expeditions, observations while hunting and game keeping, or for personal safety – with MINOX night vision devices, the night is literally turned into day!



FULLY DIGITAL.

NVD 650

OBSERVE, PHOTOGRAPH, RECORD — OUR DIGITAL SOLUTION FOR THE NIGHT



FEATURES

- 6x magnification (optical), 5x digital (= max. 30x magnification)
- Powerful IR emitter (850 nm wavelength): range up to 350 m
- Can be used during the day
- Rail for additional IR lighting

LEARN MORE ONLINE



BRINGS LIGHT INTO THE DARKNESS

NV 351

MORE SAFETY AND ORIENTATION IN DEEP DARKNESS AT SHORT DISTANCES



FEATURES

- 2.5x magnification
- Powerful light amplifier tube with a range of up to 70 meters
- Light, compact and handy
- Robust and reliable
- Tripod mount

LEARN MORE ONLINE



YOUR TRAIL CAM. YOUR MINOX.

OUR TRAIL CAMERAS FOR HUNTERS

For a long time now, trail cameras have been used to monitor, record and scout nature and wildlife in hunting grounds. Even for nature observation, they have become an indispensable tool for the care and attention of wildlife. What is more, they are also perfect for garden or home surveillance.

So that you can leave your wildlife and surveillance camera alone for several days or even weeks in the outdoors, we rely on sophisticated technology and precise workmanship. This makes MINOX trail cameras robust and resistant for use under tough conditions.



SMART MULTI-TALENT

DTC 1200

Unlimited photos, cloud storage, operation via app, GPS transmitter - with the DTC 1200, a trail camera with 4G transmission, MINOX is entering completely new territory. By implementing an innovative operating concept which includes a SIM card and user-friendly smartphone app, the cumbersome configuration of trail cameras with a transmission function is now a thing of the past. Always benefit from the optimal mobile network in all hunting grounds thanks to national roaming and save valuable battery life at the same time. And this with an unlimited number of images at a fixed monthly price. In combination with the app you can also share your images easily, safely and without limitation with other hunters. Also clever: the GPS function makes it possible to locate the camera at any time.





MINOX SIM CARD WITH UNLIMITED DATA VOLUME AND NATIONAL ROAMING

€14,99* PER MONTH

*Current costs: € 14.99 per month (incl. VAT), monthly cancelable, price subject to change. Further information and current tarrif: minox.com/app-dtc1200





FEATURES

- True 4G broadcast standard
- Innovative operating concept with SIM card (included)
- User-friendly app to receive and share photos sent from camera
- With national roaming, always connected to the best mobile network in all hunting grounds
- Unlimited number of photos at a flat monthly fee
- Data storage in Germany
- 60 LEDs with 940 nm for a range up to 20 m
- Shutter release 0.6 sec.
- Photo resolution up to max. 20 MP
- GPS function to locate camera's exact location
- Battery magazine for easy change of batteries

LEARN MORE ONLINE



HIGH-TECH IN DISGUISE

DTC 460

Conspicuously inconspicuous, the new DTC 460 wildlife and observation camera blends in perfectly with its surroundings. Once you have attached the photo trap to a tree, it becomes one with the bark structure and is hardly recognizable. In use, it boasts of state-of-the-art electronics optimized for outstanding nighttime operation, and innovative Hi-Beam LEDs for photo and video sequences in all light conditions. The practical bar magazines make it easy to change batteries - even with clammy fingers in cold and wet temperatures. Optionally, the front panels can be easily replaced so that you can adapt your master of disguise to the environment.



*3 optional front panels for the perfect disguise in the wilderness.

FEATURES

- Interchangeable front panels to adapt to various surroundings.

 One front panel with a rough bark pattern is included in delivery
- Bar magazines for quick battery changes
- Slim housing only approx. 34 mm deep
- Data storage on SD/SDHC card up to max. 32 GB
- Shutter release 0.7 sec.
- Photo resolution up to max. 12 MP

LEARN MORE ONLINE



RELIABLE OBSERVER

DTC 550 WiFi

Whether used as a photo trap at a food plot or game trail, or to observe nesting activities or even for property surveillance, this camera can do it all. The WIFI connection and app provide the easy transfer of images and videos to your smartphone. With an extremely fast shutter release of just 0.4 seconds, the MINOX DTC 550 WiFi wildlife and surveillance camera hardly misses a single thing. Additionally, you can record HD videos with sound at resolutions of up to 1080p. At night, 42 black LEDs provide sufficient light to capture images. At a wavelength of 940 nm, they cannot be perceived by humans or animals, keeping the camera concealed at all times.









FEATURES

- Convenient data transfer and control of camera system settings via WiFi connection and app (within a radius of 10 m)
- Invisible IR flash with 15 meters range
- HD video resolution (1080p)
- Trigger release: 0.4 sec.
- Up to 9 photos per burst and videos up to 3 minutes length
- 2.4" color display
- Timer function
- Battery life up to 6 months
- Robust and weather-resistant polycarbonate housing
- Port for external power supply
- Splashproof according to IP54

LEARN MORE ONLINE



OUTDOOR ALL-ROUNDER

DTC 395

With the MINOX DTC 395 wildlife and observation camera, you have everything in view, at home and in your hunting grounds – at all times! It delivers outstanding image quality by day or night with sharp details, high contrast and natural color rendition. In addition to single photos, you can also record videos in full HD resolution. The powerful infrared flash with >940 nm provides you with reliable images in the dark or under unfavorable lighting conditions up to a distance of 15 meters, and is completely invisible to humans and animals.





FEATURES

- Invisible IR flash with 15 meters range
- Photo resolution up to max. 12 MP
- Full HD video resolution
- Trigger release: 0.7 sec.
- 2.4" color display
- Battery life up to 6 months
- Robust and weather-resistant polycarbonate housing
- Port for external power supply
- Splashproof according to IP54

LEARN MORE ONLINE



| MINOX hunting product range 2020

ACCESSORIES



FRONT PANEL #1

For the model

MINOX DTC 460



FRONT PANEL #2
For the model
MINOX DTC 460



FRONT PANEL #3

For the model

MINOX DTC 460



BAR MAGAZINE SET

For the model

MINOX DTC 460



For the model
MINOX DTC 1200



UNIVERSAL

Perfect for hands-free observation, especially at long distances.

Suitable for all MINOX binoculars.

TRIPOD ADAPTER




SAFETY KITSuitable for all MINOX trail cams



For the models
DTC 550 / DTC 550 WiFi



BINOCULAR STRAP
EASY SLIDER
Adjust and fix the strap length
with just one finger.




BINOCULAR STRAP PROFESSIONAL For swing-free carrying of binoculars.




OPTICS
CLEANING KIT
For a clear view.


RETICLE SUBTENSIONS




| | 1-5x24 | 2-10x50 | 3-15x56 |
|---|--------|---------|---------|
| Α | 200 | 100 | 66.6 |
| В | 10 | 5 | 3.3 |
| C | 2 | 1 | 0.7 |
| D | 2 | 1 | 0.7 |


All dimensions in cm at 100 m






RETICLE SUBTENSIONS









All dimensions in Milliradiant (mrad)

RETICLE SUBTENSIONS





TECHNICAL DATA RIFLESCOPES

FIND THE DETAILED DIMENSIONS ONLINE.

ALLROUNDER





LONG-RANGE



| | PRO | | | | | | |
|---|--------------------------------|--|--|--|--|--|--|
| MODEL | ZP5 3-15x50 | ZP5 5-25x56 | | | | | |
| Magnification | 3-15x | 5-25x | | | | | |
| Objective diameter (mm) | 50 | 56 | | | | | |
| Exit pupil min / max (mm) | 11.5 / 3.33 | 12.0 / 4.4 | | | | | |
| Field of view min / max at 100 m (m) | 12.8 / 2.8 | 14.0 / 4.7 | | | | | |
| Eye relief (mm) | 90 | 90 | | | | | |
| Diopter adjustment | -3 / +2.5 | -3 / +2.5 | | | | | |
| Reticle adjustment (per click) | 0.1 mrad | 0.1 mrad | | | | | |
| Reticle adjustment (elevation) | 28 mrad | 28 mrad | | | | | |
| Reticle adjustment (windage) | ± 6 mrad | ± 6 mrad | | | | | |
| Illuminated reticle | Yes | Yes | | | | | |
| Reticle | MR2, MR5 | MR2, MR4, MR5, THLR | | | | | |
| Focal plane | 1st | 1st | | | | | |
| Power source for illuminated reticle | 1x CR 2032 | 1x CR 2032 | | | | | |
| Parallax compensation | 50 m to ∞ | 50 m to ∞ | | | | | |
| Nitrogen gas purged | Yes | Yes | | | | | |
| Non-fogging, waterproof according to IPX7 | Yes | Yes | | | | | |
| Tube diameter (mm) | 34 | 34 | | | | | |
| Length (mm) | 345 | 415 | | | | | |
| Weight (g) | 920 | 970 | | | | | |
| MINOX Comfort Service | Yes | Yes | | | | | |
| Order no. | 80106546 (MR2), 80106547 (MR5) | 80106549 (MR2), 80106552 (MR4), 80106550 (MR5), 80106551 (THLR) | | | | | |

| ALLROUNDER LONG | | | | | | | | |
|--|--|--|-----------------|--|--|--|--|--|
| 1-5x24 | 2-10x50 | 3-15x56 | 5-25×56 LR | | | | | |
| 1-5x | 2-10x | 3-15x | 5-25x | | | | | |
| 24 | 50 | 56 | 56 | | | | | |
| 11.4 / 4.9 | 11.4 / 5.2 | 11.4 / 3.8 | 10.6 / 2.3 | | | | | |
| 37.1 / 8.2 | 18.9 / 4.0 | 11.9 / 2.3 | 7.2 / 1.6 | | | | | |
| ~100 | ~100 | ~100 | ~95 | | | | | |
| ±2 | ±2 | ±2 | -4 / +2.2 | | | | | |
| 1 cm (at 100 m) | 1 cm (at 100 m) | 1 cm (at 100 m) | 1 cm (at 100 m) | | | | | |
| ±100 cm | ±100 cm | ±55 cm | ±140 cm | | | | | |
| ±100 cm | ±100 cm | ±55 cm | ±60 cm | | | | | |
| Yes | Yes | Yes | Yes | | | | | |
| Illuminated reticle #4 | Illuminated reticle #4 | Illuminated reticle #4 | LR | | | | | |
| 2nd | 2nd | 2nd | 1st | | | | | |
| 2x CR2032 | 2x CR2032 | 2x CR2032 | 1x CR 2032 | | | | | |
| 100 m | 100 m | 50 m to ∞ | 50 m to ∞ | | | | | |
| Yes | Yes | Yes | Yes | | | | | |
| Yes | Yes | Yes | Yes | | | | | |
| 30 | 30 | 30 | 34 | | | | | |
| 285 | 335 | 372 | 430 | | | | | |
| 480 | 650 | 760 | 940 | | | | | |
| Yes | Yes | Yes | Yes | | | | | |
| 80107662 (without rail), 80107666 (with rail) | 80107663 (without rail), 80107667 (with rail) | 80107664 (without rail), 80107672 (with rail) | 80107665 | | | | | |

^{*} According to spectral transmission DIN ISO 14490-5

TECHNICAL DATA BINOCULARS

| | | X-HD | | | | | X-A | CTIVE | | | | | | X-LITE | | | | RAPID |
|---------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| MODEL | 8x44 | 10x44 | 8x56 | 8x25 | 10x25 | 8x33 | 10x33 | 8x44 | 10x44 | 8x56 | 8x26 | 10x26 | 8x34 | 10x34 | 8x42 | 10x42 | 8x56 | 7.5x44 |
| Magnification | 8x | 10x | 8x | 8x | 10x | 8x | 10x | 8x | 10x | 8x | 8x | 10x | 8x | 10x | 8x | 10x | 8x | 7.5x |
| Entry pupil (mm) | 44 | 44 | 56 | 25 | 25 | 33 | 33 | 44 | 44 | 56 | 26 | 26 | 34 | 34 | 42 | 42 | 56 | 44 |
| Exit pupil (mm) | 5.5 | 4.4 | 7 | 3.1 | 2.5 | 4.1 | 3.3 | 5.25 | 4.4 | 7 | 3.25 | 2.6 | 4.25 | 3.4 | 5.25 | 4.2 | 7 | 5.9 |
| Interpupillary distance (mm) | 57-78 | 58-75 | 57-78 | 56-78 | 56-78 | 58-78 | 58-78 | 56-73 | 56-73 | 56-76 | 56-72 | 56-72 | 56-76 | 56-76 | 56-76 | 56-76 | 60-76 | 56-78 |
| Field of view at 1,000 m (m) | 136 / 7.8° | 115 / 6.5° | 126 / 7.2° | 121 | 105 | 140 | 115 | 136 | 115 | 126 | 119 | 98 | 124 | 105 | 124 | 106 | 112 | 132 |
| Close focus (m) | 2.5 | 2.5 | 3.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 3.5 | 3 | 4 | 3 | 3 | 3 | 3 | 3 | 1.5 |
| Diopter adjustment (dpt.) | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 4 | ± 3 | ± 3 | ± 3 | ± 3 | ± 3 | ± 3 | ± 3 | -2 / +5 |
| Operating temperature °C | -10° to +50° |
| Waterproof according to IPX7 | Yes |
| Dimensions (mm HxWxD) | 150x130x53 | 150x130x53 | 195x160x70 | 113x114x35 | 113x114x35 | 138x130x45 | 138x130x45 | 150x133x53 | 150x133x53 | 195x160x70 | 117x113x35 | 117x113x35 | 133x124x43 | 133x124x43 | 145x121x52 | 145x121x52 | 166x147x66 | 150x131x53 |
| Weight (g) | 720 | 720 | 1.250 | 325 | 325 | 570 | 570 | 720 | 720 | 1.280 | 290 | 290 | 450 | 450 | 610 | 590 | 970 | 780 |
| Order no. | 80107486 | 80107487 | 80107488 | 80407330 | 80407331 | 80407333 | 80407334 | 80407335 | 80407336 | 80407337 | 80407325 | 80407326 | 80408167 | 80408168 | 80407327 | 80407328 | 80407329 | 80405445 |

TECHNICAL DATA

RED DOT SIGHT

| MODEL | RV 1 |
|------------------------------|--|
| Magnification | 1x |
| Aperture | 18 mm |
| Adjustment travel | 100 MOA |
| Adjustment per click | 1 MOA |
| Red dot size | 2 MOA |
| Red dot settings | - 12 levels 0 = off, - 1-3 = night settings, - 4-10 = daylight settings, - 11 = extra bright daylight setting |
| Battery | CR 2032, 3 Volt |
| Battery life | Up to 50,000 hours through LED technology |
| Waterproof according to IPX7 | Yes |
| Weight | 96 g (without mount) |
| Dimensions (LxWxH) | 64x43x37 mm |
| Order no. | 80224005 |

TECHNICAL DATA SPOTTING SCOPES

| MODEL | MD 60 ZR / MD 80 ZR | MD 50 W |
|------------------------------|------------------------------|----------------|
| Magnification | 12x - 40x / 20x - 60x | 16x - 30x |
| Field of view at 1,000 m | 59 m / 19 m i.e. 40 m / 14 m | 47 m / 32 m |
| Close focus | 3.5 m / 7 m | 5 m |
| Operating temperature | 10° to +45° C | -14° to +40° C |
| Waterproof according to IPX7 | Yes | Yes |
| Weight | 1,620 g / 2,190 g | 690 g |
| Comfort Service | Yes | Yes |

TECHNICAL DATA TRAIL & SURVEILLANCE CAMERAS

| MODELL | DTC 1200 | DTC 550 WiFI | | | |
|---------------------------------|---|---|--|--|--|
| Category | Trail camera with 4G transmission and preinstalled SIM card | Trail camera with data transfer via WiFi | | | |
| Control via app | Yes (free of charge, Android and iOS) | Yes (free of charge, Android and iOS) | | | |
| GPS locating | Yes | No | | | |
| Invisible IR flash with range | Up to 20 m | Up to 15 m | | | |
| Trigger release | 0.6 sec. | 0.4 sec. | | | |
| Photo resolution | Up to max. 20 MP | Up to max. 16 MP | | | |
| External memory | SD / SDHC card up to 32 GB | SD / SDHC card up to 32 GB | | | |
| Display | 2.0" TFT color display | 2.4" TFT color display | | | |
| Powerful IR flash | 15 m range, No Glow 940nm, adjustable: 3, 5, 8, 12, 16, 20 MP | 20m range, Low Glow 850nm, adjustable: 0.3, 2, 4, 8, 12, 16MP | | | |
| Photo burst per trigger release | 1-10 (adjustable) | 1-9 (adjustable) | | | |
| Video resolution | 1920x1080 (30fps), 1280x720 (30fps), 848x480 (30fps) | 1920x1080 (15 und 30fps), 1280x720 (30fps), 848x480 (30fps), 720x480 (30fps) | | | |
| Video length | 5 – 60 sec. (adjustable) | 10 sec. – 3 Min. (adjustable) | | | |
| File formats | JPG / AVI | JPG / AVI | | | |
| Timestamp | Date, time, trigger event, moon phase, temperature, battery status | Date, time, temperature, battery status, moon phase, camera name | | | |
| Images by day | Color | Color | | | |
| Images by night | Black/white | Black/white | | | |
| User-friendly interface | per App | App and 10-button controls | | | |
| Exposure | Auto | Auto | | | |
| Password protection | No, locked via app | 4-digit combination | | | |
| Real-time display viewing | Yes, to position camera | Photo / video playback | | | |
| Standby time | Approx. 6 months (12x 1.5V AA batteries) | Up to 6 months (8x 1.5V AA batteries) | | | |
| Microphone | Integrated | Integrated | | | |
| Ports | USB, 6V / 2A DC | USB, 6V DC (min. 2000 mA) | | | |
| Power supply | 12x 1.5 AA batteries, alkaline, lithium or NiMH batteries, | 8x 1.5 AA batteries, alkaline, lithium or NiMH batteries or 6V external power supply | | | |
| External power supply | Yes, 6V / 2A DC | Yes, 6V / 2A DC | | | |
| Tripod mount | Yes | Yes | | | |
| Splashproof | Yes | Yes | | | |
| Included in delivery | Trail camera with preinstalled SIM card, 4G antenna, 16 GB microSD card with SD adapter, mounting strap | Trail camera, mounting strap, USB cable, wall mount | | | |
| Weight (without batteries) | Approx. 460 g | Approx. 290 g | | | |
| Order no. | 80406283 | 80407270 | | | |

| DTC 550 | DTC 460 | DTC 395 | | | |
|---|--|--|--|--|--|
| Trail camera | Trail camera with exchangeable front panel | Trail camera | | | |
| No | No | No | | | |
| No | No | No | | | |
| Up to 15 m | Up to 15 m | Up to 15 m | | | |
| 0.4 sec. | 0.7 sec. | 0.7 sec. | | | |
| Up to max. 12 MP | Up to max. 12 MP | Up to max. 12 MP | | | |
| SD / SDHC card up to 32 GB | SD / SDHC card up to 32 GB | SD / SDHC card up to 32 GB | | | |
| 2.4" TFT color display | 2.4" TFT color display | 2.4" TFT color display | | | |
| range 15 m, No Glow 940nm, adjustable: 0.5, 2, 4, 8, 12MP | Up to 15 m range, Low Glow 850nm, adjustable: 0.5, 2, 4, 8, 12MP | range 15 m, adjustable: 12 MP, 8 MP, 5 MP | | | |
| 1-9 (adjustable) | 1-3 (adjustable) | 1-3 (adjustable) | | | |
| 1920x1080, 1280x720, 848x480, 720x480 | 1920×1080 (30fps), 1280×720 (30fps), 848×480 (30fps), 640×480 VGA (30 fps) | 1920x1080 (30fps), 1280x720 HD (30fps) - Default, 848x480 (30fps), 640x480 (30fps) | | | |
| 10 sec. – 3 Min. (adjustable) | 10 – 60 sec. (adjustable) | 10 – 60 sec. (adjustable) | | | |
| JPG / AVI | JPG / AVI | JPG / AVI (MJPG) | | | |
| Date, time, temperature and moon phase, camera name | Date, time, temperature and moon phase | Date, time, temperature and moon phase | | | |
| Color | Color | Color | | | |
| Black/white | Black/white | Black/white | | | |
| 10-button controls | 10-button controls | 10-button controls | | | |
| Auto | Auto | Auto | | | |
| 4-digit combination | 4-digit combination | 4-digit combination | | | |
| Photo / video playback | Photo / video playback | Photo / video playback | | | |
| Up to 6 months (8x 1.5V AA batteries) | Up to 6 months (8x 1.5V AA batteries) in 2 separate removable bar magazines | Up to 6 months (8x 1.5V AA batteries) | | | |
| Integrated | Integrated | Integrated | | | |
| USB, 6V DC (min. 2000 mA) | USB | USB, 6V DC (min. 2000 mA) | | | |
| 8x 1.5 AA batteries, alkaline, lithium or NiMH batteries or 6V external power supply | 8x 1.5 AA batteries, alkaline, lithium or NiMH batteries, 2 exchangeable battery magazines | 8x 1.5 AA batteries, alkaline, lithium or NiMH batteries or 6V external power supply | | | |
| Yes, 12V / 1A DC | No | Yes, 6V / 2A DC | | | |
| Yes | Yes | Yes | | | |
| Yes | Yes | Yes | | | |
| Trail camera MINOX DTC 550, mounting strap, USB cable, wall mount, instruction manual | Trail camera MINOX DTC 460 with standard front panel, mounting strap, wall mount, USB cable, Quickstart guide, saftey instructions | Trail camera, mounting strap, USB cable, wall mount | | | |
| Approx. 290 g | Approx. 415 g | Approx. 280 g | | | |
| 80405434 | 80406281 | 80405444 | | | |

TECHNICAL DATA


NIGHT VISION DEVICES

| MODEL | NVD 650 | NV 351 | | |
|---------------------------|---|---------------------------|--|--|
| Magnification | 6x (optical), up to 30x (combinded with digital zoom) | 2.5x | | |
| Type of operation | Digital | Tube type: Gen 1+ | | |
| Powerful IR light emitter | Range up to 350 m | Range up to 70 m | | |
| Operating temperature | -30° to +55°C | -30° C to +50° C | | |
| Power source | 4x 1.5 V AA batteries / alkaline, lithium or NiMH batteries | 1x CR 123 lithium battery | | |
| Video output | NTSC or PAL | - | | |
| External memory | microSD / microSDHC card up to 32 GB | - | | |
| Weight | 765 g | 335 g | | |
| Dimensions (HxWxD) | 62x105x208 mm | 170x79x50 mm | | |

AT

EYE LEVEL

EXPERIENCE THE NEW WORLD OF MINOX



www.minox.com

VISIT US ALSO ON







MINOX



Find more information on our products and discover the whole MINOX product range on our website at www.minox.com

MINOX GmbH

Ziegelstadel 20 · D-88316 Isny im Allgäu Phone +49 (0) 64 41 / 917 - 0 info@minox.com

Service & Support

Wilhelm-Loh-Str. 1 · D-35578 Wetzlar Phone +49 (0) 64 41 / 917 - 700 service@minox.com

 $facebook.com/minox.optics \cdot youtube.com/minox \cdot instagram.com/minox.optics$