

ABOUT VANGUARD

THE YEAR WAS 1986. Vanguard was a brand-new camera tripod maker

with a small manufacturing facility. The company's odds for success in a crowded market were slim, but this didn't stop a determined young woman from believing in her fledgling business. Today, Vanguard is a global company that designs and manufactures tripods, bags, sporting optics, and accessories.

Vanguard has a team of the industry's brightest product engineers working at robust research and development facilities. By definition, Vanguard means "to lead", and our brand is fully committed to its mission of providing high-quality products with game-changing features. Our ability to support our customers at every stage of the product development process is what has allowed us to become a leader in the industry. As a global leader in photo and outdoor accessories, Vanguard believes in a responsibility to play a positive role in the communities and environments in which we operate and serve.



VANGUARD HUNTING

HISTORY OF VANGUARD

	ABOUT VANGUARD
	TABLE OF CONTENTS
	FACTORY
	NEW PRODUCTS
	RIFLE SCOPES
	ENDEAVOR RS IV
	ENDEAVOR RS VI
	SPOTTING SCOPES
	ENDEAVOR HD
	VEO HD2 VESTA
ı	
ı	OPTICAL ACCESSORIES I
ı	BINOCULARS VEO HD 2 2
ı	VEO HD 2 2
ı	VEO HD 2
ı	VEO ED 20 VESTA 20
ı	MUNUCIII ADG
ı	MONOCULARS VEO HD2 IO42M 2
ı	VESTA 8320M 2
۱	TRIPODS ALTA PRO 2 31 VEO 3T 3
ı	ALTA PRO 2 31
١	VEO 3T3
ı	VEO 3 3 VEO 2 PRO 3
ı	VEO 2 PRO AV/CV 3
	VEO 3 GO 3
۱	VESTA FB 3
	VESTA 3

SHOOTING SUPPORTS					
EQUALIZER	 	-	-	-	-41
QUEST					
SCOUT	 	-	-	-	43
PORTA-AIM	 	-	-	-	44
ESPOD CX 1 / 1 OS	 	-	-	-	44
VEO 2	 	-	-	-	45
U-YOKE	 	-	-	-	45
HEADS & ACCESSORIES					
ALTA PH PAN HEADS	 	_	_	_	47
VEO 2 PH PAN HEADS					
VEO 2 WINDOW MOUNTS					
PH WINDOW MOUNTS					
VESTA TTI					
VS-82	 	-	-	-	49
QUICK SHOES					
ENDEAVOR LDA	 	-	-	-	50
VEO MT-I2	 	-	-	-	51
VEO+MAI	 	-	-	-	51
OPTIC GUARD/OPTIC GUARD CAMO	 	-	-	-	52
BA-185 VEO PA-10	 	-	-	-	52
VEO PA-10	 	-	-	-	52
50MM SUNSHADE	 	-	-	-	52
SPEED MAG LEVER	 	-	-	-	52
30 MM RS RINGS					
SUPREME					
ENDEAVOR SLINGS	 	-	-	-	54
SPORTING OPTICS KEY FEATURES	 	-	-	-	55
RETICLES	 	-	_		56
SPEC SHEET					
SEE SUCCI				_	JŌ

HEADS & ACCESSORIES


EACTORY

Growing into a global leader since its founding in 1986, VANGUARD provides more than our competitors because we are the factory. There are no third-party factories, development or design firms or other outsourcing of any kind in the process. More than 1,000 Vanguard employees create the products and power the brand within our robust global operation. Every step of the process is orchestrated by Vanguard's in-house R & D, production, administration, marketing and sales teams in Vanguard-owned and controlled facilities. This enables us to ensure standout product quality and to eliminate "middle men." The result is higher value for customers, higher margins for retailers, and greater efficiency in direct communication with the manufacturer for everyone.











TOTAL PRODUCT OWNERSHIP FROM IDEA TO FINSHED PRODUCT

UNMATCHED QUALITY CONTROL

Vanguard founders credit our success to the people across the globe who have given supportive and valuable feedback about product features and price points over our three decades. This focus on listening to the market's needs and wants has inspired us to create products with first-of-its-kind features, notable reliability and impressive price points. Notable industry publications and media have consistently recognized our products' quality and performance. We're privileged to have earned top honors from the Technical Image Press Association, the Red Dot Design Award, iF Design Award, the Industrial Designers Association of America, Gmark, and other respected global associations

TRIPODS

SHOOTING SUPPORTS HEADS & ACCESSORIES

RIFLE SCOPES

"CHECK-OUT 2021" WHAT IS NEW IN 2021 "CHECK-OUT

VANGUARD LISTENS TO THE VOICE OF CONSUMERS AND CONTINUOUSLY INVESTS IN RESEARCH AND DEVELOPMENT TO PROVIDE A GREAT OUTDOOR EXPERIENCE

VEO ED P24

VEO 3T P32

2021

VEO HD 2 P22



VEO + MA 1 P51





VEO HD P23



VEO 3 P34







VEO MT-I2 P5



VANGUARD



RETICLES

VANGUARD 6

♥VANGUARD 7



ENDEAVOR RS IV

Acclaimed Vanguard quality in a European tube design to meet the performance requirements of both the aspiring and professional user. Exceptional image quality, multilayer anti-reflective coatings, and premium ED glass. Large fields of view and a rapid focus eyepiece deliver a positive experience. The single piece, high-grade 30MM tube has a robust, anti-scratch, anodized matte surface. Nitrogen purged against dust and moisture, and recoil resistant to provide a lifetime of dependability and success. Precise windage and elevation adjustments offer reset capability with a parallax system















Advanced **MultiGuard®** Coatings for Higher Light Transmittance



Offers Illuminated Reticles with Replaceable Battery



Waterproof and Fogproof

WHAT'S INCLUDED



Protective Lens Covers

MODEL	RETICLE	ILLUM.	FIELD OF VIEW	TUBE	EYE RELIEF	WEIGHT	LENGTH
ENDEAVOR RS IV I-4X24 G	GERMAN 4		II6.4 - 27.1 FT /IOO YDS 38.8 - 9 M /IOO M	30 MM	105 - 92 MM	17.6 OZ 508G	II IN 281 MM
ENDEAVOR RS IV 1.5-6X42 G	GERMAN 4		70.5 - I5.6 FT /I00 YDS 23.5 - 5.2 M /I00 M	30 MM	104.5 - 90 MM	22.2 OZ 630 G	II.9 IN 303 MM
ENDEAVOR RS IV 2-8X32 D	DUPLEX		49.6 - 13.1 FT /100 YDS 16.5 - 4.4 M /100M	30 MM	105 - 90 MM	17.60Z 500G	12 IN 305 MM
ENDEAVOR RS IV 2.5-10X50 G	GERMAN 4		44 - II FT / IOO YDS I5 - 4 M /IOOM	30 MM	102 - 92 MM	24 OZ 680 G	14 IN 355 MM
ENDEAVOR RS IV 2.5-10X50 DS6	DISPATCH 600		44 - II FT / IOO YDS I5 - 4 M /IOOM	30 MM	102 - 92 MM	24 OZ 680 G	14 IN 355 MM
ENDEAVOR RS IV 3-12X56 G	GERMAN 4		37.5 - 9.1 FT /100 YDS 12.5 - 43M /100M	30 MM	105 - 90 MM	25 OZ 720 G	14.1 IN 358 MM
ENDEAVOR RS IV 4-16X44 D	DUPLEX		27.I - 6.5 FT /IOO YDS 9 - 2.2 M /IOOM	30 MM	102 - 90 MM	24 OZ 670 G	13.2 IN 336 MM
ENDEAVOR RS IV 4-16X44 DS6	DISPATCH 600		27.I - 6.5 FT /IOO YDS 9 - 2.2 M /IOOM	30 MM	102 - 90 MM	24 OZ 670 G	13.2 IN 336 MM
ENDEAVOR RS IV 4-16X44 DS8	DISPATCH 800		27.I - 6.5 FT /IOO YDS 9 - 2.2 M /IOOM	30 MM	102 - 90 MM	24 OZ 670 G	13.2 IN 336 MM
ENDEAVOR RS IV 4-16X50 D	DUPLEX		26.I - 6.9 FT /IOO YDS 8.7 - 2.3 M /IOOM	30 MM	104 - 90MM	24 OZ 740G	14.5 IN 368 MM
ENDEAVOR RS IV 4-16X50 DS6	DISPATCH 600		26.I - 6.9 FT /IOO YDS 8.7 - 2.3 M /IOOM	30 MM	104 - 90 MM	24 OZ 740G	14.5 IN 368 MM
ENDEAVOR RS IV 4-16X50 DS8	DISPATCH 800		26.I - 6.9 FT /IOO YDS 8.7 - 2.3 M /IOOM	30 MM	104- 90 MM	24 OZ 740G	14.5 IN 368 MM
ENDEAVOR RS IV 5-20X50 D	DUPLEX		21.9 - 5.6 FT /100 YDS 7.3 - 1.9M /100M	30 MM	105 - 90 MM	25.7 OZ 730 G	14.8 IN 375 MM
ENDEAVOR RS IV 5-20X50 DSV	DISPATCH VARMINT		21.9 - 5.6 FT /100 YDS 7.3 - 1.9M /100M	30 MM	105 - 90 MM	25.7 OZ 730 G	14.8 IN 375 MM

TRIPODS

RETICLES

ENDEAVOR RS VI


The Endeavor RS VI offers illuminated German #4 and Dispatch ballistic reticles. Engineered to handle rugged terrain in the most challenging conditions, Endeavor RS VI delivers the excellence in innovation and technology with 6 times zoom. Fast on target with a true 1X magnification and 6 times zoom magnification range for total tactical versatility. Lightweight and compact to complement the lines of any MSR rifle. Multi-stage illumination feature assists with on target capability from bright sunlight to clearing dark rooms.

ENDEAVOR RS VII

The Endeavor RS VII complements any MSR rifle. The Endeavor RS VII offers illuminated German #4 and Dispatch ballistic reticles. Multi-stage illumination feature assists with on target capability from bright sunlight to clearing dark rooms. Generous 44MM objective size for easy application in low light. Engineered to handle rugged terrain in the most challenging conditions.









WHAT'S INCLUDED



Precise Windage & Elevation Adjustment with Zero Reset Feature



Offers Illuminated Reticles with Replaceable Battery



Rapid Focus Eyepiece



Protective Lens Covers

Precise Windage & Elevation Adjustment with Zero Reset Feature



Offers Illuminated Reticles with Replaceable Battery



Premium HOYA ED Glass Provides True Color and Edge to Edge Clarify



WHAT'S INCLUDED

SPECIFICATIONS

MODEL	RETICLE	ILLUM.	FIELD OF VIEW	TUBE	EYE RELIEF	WEIGHT	LENGTH
ENDEAVOR RS VI 1642 G	GERMAN 4		116.4 -17.75FT 100 YDS 38.8-5.92 M 100 M	30MM	105 - 90 MM	18.8 OZ 535G	II IN 281 MM
ENDEAVOR RS VI 1624DS556	DISPATCH TAC556		II6.4 - I7.75FT /IOO YDS 38.8-5.92 M /IOO M	30MM	105 - 90 MM	18.8 OZ 535G	II IN 281 MM

	MODEL	RETICLE	ILLUM.	FIELD OF VIEW	TUBE	EYE RELIEF	WEIGHT	LENGTH
۹	ENDEAVOR RS VII 1744 G	GERMAN 4		91.35-12.27FT /100 YDS 30.45-4.09M /100 M	30MM	96-88 MM	22.8 OZ 647 G	II.06 IN 296.2 MM
	ENDEAVOR RS VII 1744 DS556	DISPATCH		91.35-12.27FT /100 YDS 30.45-4.09M /100 M	30MM	96-88 MM	22.8 OZ 647 G	II.06 IN 296.2 MM



HEADS & ACCESSORIES

RETICLES

ENDEAVOR HD

Built-In sunshield eliminates

Glare in Direct sunlight

The angled view Endeavor HD spotting scope combines a nitrogen-filled magnesium housing and a fully multi-coated optical system to create a well-equipped zoom scope for intermediate to long-range observation. The optical system employs Extra Low Dispersion (ED) Glass to ensure accurate color rendition and virtually eliminate color fringing. The lenses are fully multicoated to ensure optimum light transmission and feature a phase-coated BAK4 roof prism. It also provides a very impressive field of view. In addition to the image quality and weather-sealed construction, the Endeavor HD includes several features that enhance the scope's functionality. It features an extendable rubber covered eyecup and boasts impressive eye relief even at the highest zoom settings. A built-in sunshield is included to eliminate glare in direct sunlight and it includes a padded raincoat with sling for carry and protection. Endeavor HD is also equipped with rapid focus and fine focus wheels for quick and precision fine tuning adjustments. The Endeavor HD mounts directly to Vanguard tripod heads (and others) that are equipped with the universal mounting plate without the use of a quick shoe.

FEATURES

OVANGUARD









SUGGESTED TO BUY WITH PA-202 (P19)





ALTA PH-123V (P47)



FULLY MULTI COATING



Vanguard's Advanced 7 Layer Coating effectively improves light transmission, reduces reflection, filters harmful lights.

Super hard waterproof membrane provides Scratch-resistant / waterproof / oil-proof / pressure-proof

Twist Out Eyecup



Magnification size for model shown:20-60x

Removable Eyepiece



WHATS INCLUDED Protective Carry Bag/Rain Cover



Extra-Low Dispersion Glass

Arca Swiss Compatible Mountable to Tripod

Dual Focus Controls For Fine-

Tuning Adjustments

	MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	WEIGHT
	ENDEAVOR HD 65A	15-45 X 65	144-68 FT /1,000 YDS 48-23 M /1,000 M	14.8-18 FT 4.5-5.5 M	19-20 MM	51 OZ 1.45 KG
I	ENDEAVOR HD 82A	20-60 X 82	IIO-52 FT /I.000 YDS 37-17 M /I.000 M	19.7-21.3 FT 6-6.5 M	19-20 MM	67 OZ l 1.89 KG

BINOCULARS

RETICLES

SHOOTING SUPPORTS HEADS & ACCESSORIES



The VEO HD spotting scope boasts excellent optical viewing for nature enthusiasts and outdoorsmen. It is nitrogen-filled making it waterproof/fogproof for challenging weather conditions. The lenses are all fully multi-coated to ensure optimum light transmission and is equipped with a large smooth focusing wheel for quick adjustments. The lightweight durable composite carbon material body is well balanced so whether in the field or at the range VEO HD is a must.





SUGGESTED TO BUY WITH


VEO PA-65 (P18)



ALTA PH-114V (P47)



FULLY MULTI COATING



Vanguard's Advanced 4 Layer Coating effectively improves light transmission, reduces reflection, filters harmful lights.

Super hard waterproof membrane provides Scratch-resistant / waterproof / oil-proof / pressure-proof



Available with 60 or 80mm objective lens

MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	WEIGHT
VEO HD 80A	20~60 X 80	IIO-52 FT / I000 YDS 37-17 M / I000 M	19.7-21.3 FT 6-6.5M	19-20MM	49.4 OZ 1400 G
VEO HD 60A	15~45 X 60	141-68 FT / 1000 YDS 47-23 M / 1000 M	16.4-19.7 FT 5-6M	19-20M M	38.8 OZ 1100 G



HEADS & ACCESSORIES

RETICLES

VESTA

The Vesta series of spotting scopes are recommended for anyone from the active outdoorsman to the casual observer. The Vesta 350 and 460 models are small enough to fit in the side pocket of a backpack and work great on a tabletop or shooting bench. While the Vesta 560 is better suited for stationary observation, travelers and trendsetters worldwide will also appreciate the Vanguard Vesta optics which are loaded with quality and deliver excellent value.





Quick focus adjustment allows the user to experience everything in fine-tuned detail

WHAT'S INCLUDED

Model No:350A, 350S and 460 comes with Vesta TT1 Table Tripod



Model No:560A comes with VS-82 **Tabletop Tripod**





SPECIFICATIONS

Multicoating

technology

	MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	WEIGHT
4	VESTA 350A	12~45 X 50	157~52 FT /1,000 YDS 52~17 M /1,000 M	29.5~39.4 FT 9~I2 M	II MM	21.2 OZ 600 G
	VESTA 350S	12~45 X 50	157~52 FT /1,000 YDS 52~17 M /1,000 M	29.5~39.4 FT 9~I2 M	II MM	21.1 OZ 598 G
	VESTA 460A	15~50 X 60	125~57 FT /1,000 YDS 42~19 M /1,000 M	32.8~39.4 FT 10~12 M	II MM	21.5 OZ 609 G
	VESTA 560A	15~45 X 60	104~63 FT /1,000 YDS 35~21 M /1,000 M	26.3~29.5FT 8~9 M	16~21 MM	45.7 OZ 1293 G



OPTICAL ACCESSORIES

VEO PA-65 OPTICS UNIVERSAL SMARTPHONE ADAPTOR

VEO PA-65 is a universal smartphone digiscoping kit that will fit any smartphone up to 90mm wide, and can be used with almost any spotting scope from any brand to enable you to take captivating closeup shots and share them straight to social media









SPOTTING SCOPE CAMERA ADAPTOR

PA-202 is a digiscoping adaptor designed specifically to fit Endeavor HD Spotting Scopes and allow any camera with a 52/58mm lens to be attached securely









BINDCULARS MONDCULARS









NEW PRODUCTS

SHOOTING SUPPORTS

HEADS & ACCESSORIES







The VEO HD2 Binocular features HOYA extra-low dispersion (ED) glass and phase-corrected BAK4 prisms that work together to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. Complementing the glass and prisms are an anti-reflective and fully multi-coated optical system that improves light transmission for bright and clear images with greater low-light performance.

The VEO HD Binocular features extra-low dispersion (ED) glass and phase-corrected BAK4 prisms that work together to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. Complementing the glass and prisms are an anti-reflective and fully multi-coated optical system that improves light transmission for bright and clear images with greater low-light performance.

Large Eyepiece

3 Stage Twist-Out Eyecup

Soft Grip Center Focusing Wheel for Comfortable Viewing

New advanced carbon composite material

Extra-Low Dispersion (ED) Glass

Soft Grip Center Focusing Wheel for Comfortable Viewing

Premium Mitsubishi Rubber Armor

New advanced carbon composite material

Premium HOYA ED Glass Provides A True Color Viewing Experience



















TVANGUARD





SUGGESTED TO BUY WITH BA-185 (P52)





VEO PA 65 (P18)














NEW ADVANCED CARBON COMPOSITE MATERIAL



GLASS 6 5 4 3 2 1

Vanguard's Advanced 7 Layer Coating effectively improves light transmission, reduces reflection, filters harmful lights.

Super hard waterproof membrane provides Scratch-resistant/waterproof/oil-proof/pressure-proof

SPECIFICATIONS

	MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	ADJUST. PUPILLARY	WEIGHT
4	VEO HD2 8420	8 X 42	377 FT /I,000 YDS I26 M /I,000 M	6.6 FT 2.0 M	19 MM	58-74 MM	25 OZ 710 G
	VEO HD2 1042	10 X 42	340 FT /I,000 YDS II4 M /I,000 M	6.6 FT 2.0 M	18 MM	58-74 MM	25 OZ 710 G





Vanguard's Advanced 7 Layer Coating effectively improves light transmission, reduces reflection, filters harmful lights.

Super hard waterproof membrane provides Scratch-resistant/waterproof/oil-proof/pressure-proof

MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	ADJUST. PUPILLARY	WEIGHT
VEO HD 8420	8 X 42	372 FT /I,000 YDS I24 M /I,000 M	6.6 FT 2.0 M	19 MM	58-74 MM	26.8 OZ 760 G
VEO HD 1042	10 X 42	342 FT /I,000 YDS II4 M /I,000 M	6.6 FT 2.0 M	18 MM	58-74 MM	27.1 OZ 767 G

RETICLES

SHOOTING SUPPORTS

HEADS & ACCESSORIES

VEO ED



VEO ED is a well-balanced, lightweight durable composite carbon binocular. It is 100% waterproof/fogproof, and designed to take on challenging weather conditions. Extra Low Dispersion (ED) Glass effectively reduces chromatic aberration and enhances color resolution and contrast. The VEO ED is essential for every outdoor enthusiast.


2 Stage Twist-Out Eyecup

Oversized Center Focus Wheel For Easy Control

Premium Mitsubishi Textured Rubber Armor

Phase-Corrected Roof Prisms

Extra-Low Dispersion (ED) Glass





Vesta binoculars are designed for any birder, traveller or hunter who is looking for value for money, without compromising on performance. The Vesta binoculars contain optical quality glass with an enhancing BAK4 roof prism design and multi-coating technology for crisp resolution, clarity, color fidelity and light transmission. Each binocular is manufactured and assembled with a light weight yet durable housing, and is waterproof and fogproof. The large center focus knob allows the user to experience everything in fine-tuned detail. From the packaging to the product and accessories, these new binoculars deliver the impression of a quality design while always remaining focused on

performance and most importantly your success afield.

VESTA

Twist Out Rubber Eyecups For Comfortable Viewing Large Center Focus Knob For Fast and Smooth Ease of use

Ergonomic and Durable Body

Light Weight yet Durable Housing

BAK Roof Prisms

FEATURES

















SUGGESTED TO BUY WITH

BA-185 (P52)

VEO PA 65 (P18)







Vanguard's Advanced 7 Layer Coating effectively improves light transmission, reduces reflection, filters harmful lights.

Super hard waterproof membrane provides Scratch-resistant / waterproof /oil-proof/pressure-proof

SPECIFICATIONS

MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	ADJUST. PUPILLARY	WEIGHT
VEO ED 8420	8 X 42	330 FT / 1000 YDS 110 M / 1 000 M	8.2 FT 2.5 M	19 MM	55-75MM	22.58 OZ 640 G
VEO ED 1042	10 X 42	314 FT / 1000 YDS 105 M / 1 000 M	9.2 FT 2.8 M	16 MM	55-75MM	22.58 OZ 640 G
VEO ED 1050	10 X 50	282 FT / 1000 YDS 94 M / 1 000 M	9.8 FT 3.0 M	19 MM	59.5-75MM	27.58 OZ 782 G









SUGGESTED TO BUY WITH

BA-185 (P52)

VEO PA 65 (P18)





SPECIFICATIONS

MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	ADJUST. PUPILLARY	WEIGHT
VESTA 8250	8 X 25	340 FT /I,000 YDS II4 M /I,000 M	8.2 FT 2.5 M	12.5 MM	56-74 MM	8.5 OZ 241 G
VESTA 8420	8 X 42	325 FT /I,000 YDS 108 M /I,000 M	6.9 FT 2.1 M	19 MM	56-74 MM	22.22 OZ 630 G
VESTA 1025	10 X 25	330 FT /I,000 YDS II0 M /I,000 M	8.2 FT 2.5 M	10 MM	56-74 MM	8.32 OZ 236 G
VESTA 1042	10 X 42	298 FT /I,000 YDS 100 M /I,000 M	6.9 FT 2.1 M	17 MM	56-74 MM	22.01 OZ 624 G
VESTA 1042RT	10 X 42	298 FT /I,000 YDS I00 M /I,000 M	6.9 FT 2.1 M	17 MM	56-74 MM	22.01 OZ 624 G

♥VANGUARD 24

HEADS & ACCESSORIES

RETICLES

FACTORY

NEW PRODUCTS

RIFLE SCOPES

VEO HD2 1042M



The VEO HD2 Monocular features HOYA extra-low dispersion (ED) glass to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. The package includes a smartphone adapter and bluetooth remote so you can capture crisp, clear images on the go

VESTA 8320M

The Vanguard Vesta 8320M monocular delivers optimal optical performance in a lightweight and compact body. The package includes a smart phone adapter and blue tooth remote so you can capture crisp, clear images on the go.











SPECIFICATIONS MODEL SIZE FIELD OF VIEW NEAR FOCUS EYE RELIEF WEIGHT VEO HD 2 **1042M** 10X42 342 FT /I,000 YDS | II4 M /I,000 M 6.5 FT | 2.0 M 18 MM II.5 OZ | 325 G





for IOS/Android

	SPECIFICATIONS					
	MODEL	SIZE	FIELD OF VIEW	NEAR FOCUS	EYE RELIEF	WEIGHT
4	VESTA 8320M	8X32	392 FT /I,000 YDS 131 M /I,000 M	8.2 FT 2.5 M	17.7 MM	8.820Z 250 G



HEADS & ACCESSORIES

RETICLES

NEW PRODUCTS

RIFLE SCOPES

ALTA PRO 2

ULTRA-STABLE, DURABLE, EASY TO USE, AND RELIABLE TRIPODS





ALTA PRO 2 tripods combine ultra-stability, durability, ease of use, and reliability every outdoorsman needs. With aluminum and carbon fiber models, the tripod kits include fluid pan heads or video heads dedicated to photography, videography and observation. Fast operation, intuitive, lightweight, and stable, the series offers a user experience that will meet the most demanding situations.



Stable and Strong Hexagonal Center Column



TWO WAY FLUID PAN HEAD 263AV/CV - ALTA PH-114V

TWO WAY PAN HEAD

264AO - ALTA PH-31



20°, 40°, 60°, 80° Adjustable Leg Angles



Unique "Locked/Unlocked" Twist Leg Lock System

LOW ANGLE ADAPTOR ALTA LOW ANGLE ADAPTOR **AVAILABLE SEPARATELY**





-		_			
e un	Fr:I		ΛІΙ	1010	110

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
ALTA PRO 2 264AO	27.8 IN 705 MM	63.9 IN 1622 MM	50.6 IN 1285 MM	26 MM	ALUMINUM	4	ALTA PH-31	II LBS 5 KG	5.10 LBS 2315 G
ALTA PRO 2 263AV	26.9 IN 683 MM	67.6 IN 1717 MM	54.5 IN 1385 MM	26 MM	ALUMINUM	3	ALTA PH-114V	15.4 LBS 7 KG	5.31 LBS 2410 G
ALTA PRO 2 263CV	26.9 IN 683 MM	67.6 IN 1717 MM	54.5 IN 1385 MM	26 MM	CARBON FIBER	3	ALTA PH-114V	15.4 LBS 7 KG	4.85 LBS 2200 G



SHOOTING SUPPORTS

HEADS & ACCESSORIES

NEW PRODUCTS

Cold Shoe Mount for a microphone or lighting accessory

Fits Smartphone size up

to 85mm/3.35inches

COMPACT TRAVEL, ULTRA-STABLE, DURABLE, EASY TO USE, AND RELIABLE

The VEO 3T Series is designed to deliver both portability (with models that fold to less than 16 in/41cm and weigh 3lbs/1.4kg) and performance (with a maximum height of up to 65 in/166cm and a load capacity of up to 26.5lbs/12kg). The series also includes an innovative Arca compatible ball head that has the option to attach a pan-handle for greater control, especially when using longer lenses or spotting scopes, and a quick release plate that can be used to attach a smartphone up to 3.35 in/85mm wide with additional accessories. As if that wasn't enough, each tripod has a leg that can convert to a monopod with an allweather TPU grip

Arca compatible quick release plate with built in universal **Smartphone Adaptor and Cold** Shoe mount




Low angle adapter



Bubble Level for precise positioning

Two additional 3/8" threads on the canopy allow additional accessories to be attached with a magic arm (not included)



SPECIFICATIONS



Removeable pan handle

CONVERTS TO A MONOPOD

VERSATILE ATTACHMENT ABILITY FOR

PHONE BROADCAST

1/4"thread hole for extra equipment



VEO PH-20T IDEAL FOR SPOTTING SCOPE USE





New Arca Compatible Ball Heads

The 2-section central column delivers the balance

3 easy set leg angles (20°, 50° & 80°)

between maximum height and portability

Converts to a monopod



Rubber feet& Spiked feet

VANGUARD 32

VANGUARD 33

BINOCULARS

SHOOTING SUPPORTS

HEADS & ACCESSORIES

RETICLES

VEO 3 ULTRA-STABLE, DURABLE, EASY TO USE, AND RELIABLE TRIPODS



The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a monopod



VEO 2 PRO









veo 2 ph-28 veo 2 ph-26

Removable Hook

Quick Flip Leg Locks (Aluminum Tripods Only)







Carrying Bag

Spiked Feet

Exchanger Low Angle Adapter

Hex Wrench

SPECIFICATII

33.06 LBS | 15 KG | 4.19 LBS | 1900 G

VEO BH-160S

	I LUII IUATIUNU									
	MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
	VEO2 PRO 203AO	22 IN 560 MM	57.5 IN 1460 MM	45.9 IN 1165 MM	20MM	ALUMINUM	3	VEO 2 PH-26	6.6 LBS 3 KG	3.14 LBS 1425 G
4	VEO2 PRO 233AO	22 IN 560 MM	57.5 IN 1460 MM	45.7 IN II60 MM	23MM	ALUMINUM	3	VEO 2 PH-28	8.8 LBS 4 KG	3.71 LBS 1683 G
	VEO2 PRO 233CO	22 IN 560 MM	575 IN 1460 MM	46.I IN 1170 MM	23MM	CARBON FIBER	3	VEO 2 PH-28	8.8 LBS 4 KG	3.19 LBS 1446 G
	VEO2 PRO 263AO	24 IN 610 MM	63 IN 1600 MM	50.8 IN 1290 MM	26MM	CARBON FIBER	3	VEO 2 PH-28	IILBS 5 KG	4.24 LBS 1926 G



70.67 IN | 1795 MM | 57.7 IN | 1465 MM

26MM

CARBON FIBER

♥VANGUARD 34

VEO 3 **263CB**

29.1 IN | 738 MM

HEADS & ACCESSORIES

RETICLES

SPOTTING SCOPES

VEO 2 PRO AV/CV

ULTRA STABLE, DURABLE, EASY TO USE AND RELIABLE TRIPODS



The VEO 2 PRO AV/CV models are designed for photography with longer lenses, videography or bird watching/hunting using a spotting scope. The 2-way pan-heads feature extra-large quick release plates and extended video handles for maximum control, and ergonomic locking knobs to control movement. With a choice of an Arca compatible head (VEO 2 PH-15) or a Vanguard quick release lever lock (VEO 2 PH-13) and a maximum load capacity of up to 5kg, these tripods deliver a solid and stable base



	JI LUII IUATIUNU									
	MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
	VEO2 PRO 233AV	22.8 IN 580 MM	57.5 IN 1460 MM	46.I IN II70 MM	23MM	ALUMINUM	3	VEO 2 PH-13	8.8 LBS 4 KG	3.77 LBS 1710 G
٦	VEO2 PRO 233CV	22.8 IN 580 MM	57.5 IN 1460 MM	46.3 IN 1175 MM	23MM	CARBON FIBER	3	VEO 2 PH-13	8.8 LBS 4 KG	3.29 LBS 1494 (
	VEO2 PRO 263AV	23.2 IN 590 MM	59 IN 1500 MM	47.3 IN 1200 MM	26MM	ALUMINUM	3	VEO 2 PH-15	II LBS 5 KG	4.64 LBS 2107 (

26MM

CARBON FIBER

VEO 2 PH-I5 | II LBS | 5 KG | 4.00 LBS | 1815 G

57.5 IN | 1460 MM 46.3 IN | 1175 MM

VEO 3 GO COMPACT TRIPOD + MONOPOD + SELFIE STICK + BLUETOOTH

VEO 3 GO tripods recognize the fact that many shooters don't take a tripod along because the extra bulk and weight are cumbersome. This series solves this with models that fold down to as little as 13 in/33cm and weigh as little as 1.8lbs/816g making them incredibly portable, but despite this portability there are models that can extend up to 65 in/166cm and handle up to 22lbs/10kg. The feature-rich range is available in aluminum or extremely lightweight carbon fiber, both options ideal for all types of cameras from DSLR to mirrorless/CSC/hybrid cameras and even smart phones. The included smart phone holder and Bluetooth remote turn the VEO 3 GO into a tripod or monopod/selfie stick capable of capturing images remotely with your smart phone.



	MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
	VEO 3GO 204AB	13.5 IN 345 MM	51.5 IN 1310 MM	39.7 IN 1010 MM	20MM	ALUMINUM	4	T-45	6.6 LBS 3 KG	2.08 LBS 945 G
V	VEO 3GO 204CB	13.5 IN 345MM	51.5 IN 1310 MM	39.7 IN 1010 MM	20MM	CARBON FIBER	4	T-45	6.6 LBS 3 KG	1.79 LBS 816 G
	VEO 3GO 235AB	12.9 IN 330 MM	53.5 IN 1360 MM	41.7 IN 1060 MM	23MM	ALUMINUM	5	T-50	8.8 LBS 4 KG	2.70 LBS 1225 G
	VEO 3GO 235CB	12.9 IN 330 MM	53.5 IN 1360 MM	41.7 INI 1060 MM	23MM	CARBON FIBER	5	T-50	8.8 LBS 4 KG	2.34 LBS 1065 G
	VEO 3GO 265HAB	16.1 IN 410 MM	65.5 IN 1665 MM	49.6 IN 1260 MM	26MM	ALUMINUM	5	ALTA BH-102	22.0 LBS 10 KG	3.65 LBS 1659 G
	VEO 3GO 265HCB	16.1 IN 410 MM	65.5 IN 1665 MM	49.6 IN 1260 MM	26MM	CARBON FIBER	5	ALTA BH-102	22.0 LBS 10 KG	3.II LBS 1415 G

VEO2 PRO **263CV**

22.8 IN | 580 MM

VESTA FB

COMPACT ALUMINUM TRIPODS FOR LONG LASTING PERFORMANCE






The new feature packed Vesta FB travel tripods are designed to deliver outstanding value for money, without compromising on performance. They are constructed of lightweight aluminum that weighs as little as 1.8lbs/812g and fold down to as little as 12.3 in/31.5cm for maximum portability, but include three leg angles and quick flip leg locks are quick and easy to operate. They also include a sturdy Arca compatible ball head with large ergonomic knobs which offer the ultimate flexibility in shooting, and low angle photography can be achieved by reversing the center column



Hidden hex wrench storage



ı	SF	PECIFICATIONS									
ı		MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
ı		VESTA FB 204ABS	12.3 IN 315 MM	39.7 IN 1010 MM	35.4 IN 900 MM	20MM	ALUMINUM	4	T-46	6.6 LBS 3.0 KG	1.79 LBS 812 G
	1	VESTA FB 204AB	14.7 IN 375 MM	51.1 IN 1300 MM	44.1 IN 1120 MM	20MM	ALUMINUM	4	T-46	6.6 LBS 3.0 KG	2.00 LBS 906 G
	Γ	VESTA FB 235AB	14.7 IN 375 MM	56.2 IN 1430 MM	50.2 IN 1275 MM	23MM	ALUMINUM	5	T-51	9.9 LBS 4.5 KG	2.58 LBS 1170 G

VESTA TRIPODS TRIPODS MADE FOR LONG-LASTING PERFORMANCE

The Vesta Series of tripod kits, bags, and sport optics is designed for entry-level or engaging users. In this collection you will find a variety of Vesta tripod kits. Built for performance, the Vesta Series of Tripod kits have several strong features, premium build quality, and can provide you with high to low positioning while ensuring the stability of your camera, video, or sport optic.







*PH-23 2-WAY PAN HEAD



רחו	FIO	ATI	n.	ın	
FIII	FIC	AΠ	TIP	V.S	
	1 10	/ \ II I	O,	••	

	MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
	VESTA 203AP	22.5 IN 570 MM	61 IN 1550 MM	48 IN 1220 MM	20 MM	ALUMINUM	3	PH-23	7.7 LBS 3.5 KG	2.44 LBS 1105 G
N	VESTA 204AP	20.5 IN 520 MM	61 IN 1550 MM	49.4 IN 1255 MM	20 MM	ALUMINUM	4	PH-23	7.7 LBS 3.5 KG	2.49 LBS 1132 G
	VESTA 233AP	22.91 IN 582 MM	61 IN 1550 MM	48.I IN I22I MM	23 MM	ALUMINUM	3	PH-23	7.7 LBS 3.5 KG	2.81 LBS 1275 G
	VESTA 234AP	20.67 IN 525 MM	61 IN 1550 MM	50.5 IN 1282 MM	23 MM	ALUMINUM	4	PH-23	7.7 LBS 3.5 KG	2.89 LBS 1313 G
	VESTA 203AGH	22.44 IN 570 MM	61 IN 1550 MM	48.2 IN 1255 MM	20 MM	ALUMINUM	3	GH-45	7.7 LBS 3.5 KG	2.47 LBS 1120 G
	VESTA 233AGH	22.95 IN 583 MM	61 IN 1550 MM	48.5 IN 1231 MM	23 MM	ALUMINUM	3	GH-45	7.7 LBS 3.5 KG	2.99 LBS 1360 G

HEADS & ACCESSORIES

RETICLES





Featuring rapid deployment and un beatable stability, the equalizer series takes on an array of terrains with feet that convert from metal spikes to rubber. Models enable various shooting positions from prone to sitting or kneeling.



SHOOTING SUPPORTS

EQUALIZER **EQUALIZER QS** BIPODS MADE FOR LONG-LASTING PERFORMANCE

Compact and lightweight, Equalizer is a big hit for those wanting a pivoting bipod with a low profile for quick deployment. It has a unique Pull and Position leg adjustment system that enables you to quickly and safely reposition. Metal spiked feet easily convert to rubber and provide extra stability in multiple terrains.

allows shooters to attach and detach firearms faster than ever. Hunters appreciate its quick and safely reposition. A buffer spring reduces

SDEL	ILLIC	ATIC	NIO
CDFL		: A I II	INIC

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	LEG DIAMETER	WEIGHT
EQUALIZER IQS	6.9 IN 176 MM	10 IN 255 MM	14 MM	0.7 LBS 320 G
EQUALIZER 20S	II IN 277 MM	28 IN 715 MM	17 MM	1.0 LBS 453 G
EQUALIZER 2	12.7 IN 325 MM	27 IN 685 MM	17 MM	0.9 LBS 430 G

HEADS & ACCESSORIES

RETICLES

QUEST SHOOTING SUPPORT

Quest is an all in one durable shooting stick. Quest helps you handle the elements with a soft foam, contoured hand grip and anti-slip rubber feet. It's removeable U-shaped yoke with rubber fins swivels 360° so you can make shots at every angle without repositioning the shooting stick. Remove the U-shaped yoke and use its universal ¼ thread bolt with spotting scopes or cameras.





360° "U" Yoke Provides Ultra Secure Grip



Leg Brace w/ 360° Positioning (Quest T62U only)



All Weather Foam Grips

SPECIFICATIONS

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	LEG DIAMETER	WEIGHT
QUEST T62U	27.5 IN 700 MM	62 IN 1575 MM	20 MM	2.20 LBS 1000 G
QUEST M49	22 IN 560 MM	49 IN 1245 MM	20 MM	0.66 LBS 300 G
QUEST M62	26.3 IN 670 MM	62 IN 1575 MM	20 MM	0.77 LBS 350 G
QUEST B38	19.1 IN 485 MM	38 IN 965 MM	20 MM	1.14 LBS 520 G
QUEST B62	27.1 IN 690 MM	62 IN 1575 MM	20 MM	1.43 LBS 650 G

SCOUT SHOOTING SUPPORT

Made of lightweight and durable aluminum alloy, Scout is designed for on-the-go hunters. Its V-shaped yoke is rubber-lined for greater stability for your gun, and it swivels 360 degrees for shots from any angle. Quick flip leg locks make height adjustment quick and easy. Available as a bipod or monopod.



SERIES FEATURES:







360° "V" Yoke Provides Ultra Secure Grip



Foam Grips

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	LEG DIAMETER	WEIGHT
SCOUT M62	22.0 IN 560 MM	62 IN 1575 MM	20 MM	0.57 LBS 260 G
SCOUT B62	22.2 IN 565 MM	62 IN 1575 MM	20 MM	1.10 LBS 500 G

BINOCULARS

HEADS & ACCESSORIES

Constructed of rugged aluminum, the Porta-Aim gun rest provides stable shooting support in an easily portable device for the fast-action hunter. Porta-Aim enables users to get on target—and stay there—with a 360-degree swiveling bag.

SERIES FEATURES:



Anti-Vibration Pillow





Quick Single-Handed Height

Adjustment Ring

SPECIFICATIONS

MODEL	LENGTH	WIDTH	HEIGHT	WEIGHT
PORTA-AIM	12.2 IN 310 MM	5.7 IN 145 MM	8.8-12.6 IN 225-320 MM	1.7 LBS 798 G

ESPOD CX 1 / 1 OS

TABLETOP TRIPODS

The Vanguard Espod CX 1 is a compact table tripod that is ideal for backpackers and outdoor enthusiasts. It securely holds cameras and spotting scopes up to 5.5 lb yet maintains a lightweight design so you can tote it with you on a hike or hunt. It has a two-way pan head and easy-adjust aluminum alloy 3-section legs with quick release lever locks. It has a black finish and rubber

SERIES FEATURES:



Detachable Window Mount

(1OS Model)









Quick Release Quick Shoe (1OS Model)

Quick Flip Leg Locks

SPECIFICATIONS

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	OF SECTIONS	MAX LOAD	WEIGHT
ESPOD CX I	II.6 IN 295 MM	21.3 IN 540 MM	3	5.5 LBS 2.5 KG	1.47 LBS 665 G
ESPOD CX I OS	14.8 IN 375 MM	24.4 IN 620 MM	3	6.6 LBS 3.0 KG	2.I LBS 934 G

VEO 2 SHOOTING SUPPORT

The VEO2 shooting stick is perfect for kneeling or standing when shooting a gun or crossbow. The 1/4"-20 thread can be used to support cameras, spotting scopes, binoculars, range finders, and GoPro's.









MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	LEG DIAMETER	MATERIAL	WEIGHT
VEO 2 AM-234 TU	24.4 IN 620 MM	62.6 IN 1590 MM	23 MM	ALUMINUM	1.95 LBS 885 G
VEO 2 CM-234 TU	24.4 IN 620MM	62.6 IN 1590 MM	23 MM	CARBON FIBER	1.78 LBS 809 G





HEADS & ACCESSORIES

ALTA PH FLUID PAN HEAD

Vanguard's 2-way video pan heads are built to deliver fluid motion and feature a long handle, a large quick release plate and independent operation knobs, coupled with a bubble level for the precision adjustments a professional requires. Available in two models, the ALTA PH-114V is a compact and portable Arca compatible video head, while the ALTA PH-123V delivers greater precision through the drag tension adjustment and a counterbalance system, and features a Vanguard quick release system that allows it to be set up in seconds. These fast and intuitive video heads allow you to create professional forage with







Quick Shoe







Move pan arm to either side

Includes QS-67 Quick Shoe

SPECIFICATIONS

MODEL	QUICK SHOE	FRONTAL TILT °	ROTATION °	MAX LOAD	WEIGHT
ALTA PH-114V	QS-6IP	-45°~90°	360°	17.6 LBS 8 KG	1.45 LBS 658 G
ALTA PH-123V	QS-67	-60°~90°	360°	13.2 LBS 6 KG	2.18 LBS 990 G

VEO2 PH TWO WAY PAN HEADS

The Vanguard VEO 2 PH is a 2-way pan head that allows one-handed control for video or spotting scopes, leaving your other hand free to operate controls with ease

- Simple twist handle to release/lock the smooth 2-way panning
- 360 degree rotation
- Arca compatible quick release plate with back-up safety lock



VEO2 PH-26



VEO2 PH-28

MODEL	QUICK SHOE	FRONTAL TILT°	ROTATION °	MAX LOAD	WEIGHT
VEO2 PH-26	QS-60V2	-90° TO +60°	360°	6.6 LBS 3.0 KG	0.8 LBS 365 G
VEO2 PH-28	OS-6I	-90° TO +60°	360°	II.O LBS 5.0 KG	1.1 LBS 515 G

VEO 2 WINDOW MOUNTS

With the new VEO2 window mounts by Vanguard you can cover miles of country without missing any of the details. Comfortable and smooth viewing is attained by the superior mechanical design and quality components engineered into these window mounts. Two models are available to accommodate the user's preference of either a pan head or a rotating ball head design.



VE02 BH-50WM



VEO2 PH-28WM

חדח	IFICA	ואחוד	ח
PEL	IFII.A		הו
		1101	

MODEL	LATERAL TILT°	FRONTAL TILT°	ROTATION °	WEIGHT	MAX LOAD
VEO2-PH28WM	/	-60° TO +90°	360°	1.5 LBS 711 G	8.8 LBS 4 KG
VEO2-BH50WM	-91° TO +40°	/	360°	1.4 LBS 675 G	11.0 LBS 5 KG

PH WINDOW MOUNTS

No tripod? PH pan head window mounts have unique bases and non-slip platforms. They easily attach to vehicle windows, tripods, tubular structures, blinds and others, enabling steady use of cameras, camcorders or spotting scopes for effortless





SPECIFICATIONS

♥ VANGUARD 48

MODEL	LATERAL TILT°	FRONTAL TILT°	ROTATION °	WEIGHT	MAX LOAD
PH 304	+90° TO -60°	0° TO +90°	360°	1.6 LBS 730 G	8.8 LBS 4 KG

VESTA TTI







The VESTA TT1 aluminum table top tripod kit with smart phone holder is a small, ergonomic, stable table top tripod capable of holding smart phones, sport optics, and supporting cameras up to 2kg/4.4 lbs



VS-82







The VS-82 is a compact, lightweight and convenient to use tabletop tripod. Its 2-way panhead and 360 degree rotation are ideal for spotting scope use.





ĺ	MODEL	COLOR	FOLDED HEIGHT	EXTENDED HEIGHT	MAX LOAD	WEIGHT
J	VS-82	BLACK	10.0 IN 255 MM	9.25 IN 235 MM	5.5 LBS 2.5 KG	0.94 LBS 430G

BINOCULARS

SHOOTING SUPPORTS

QS quick release plates make attaching and removing your camera a breeze, securely keeping your gear in position



QS-65

- 1/4" camera screw & pin with D-ring
- Arca compatible



- 1/4" camera screw in a removable slot & pin
- Arca compatible



QS-60S

- 1/4" camera screw & pin with D-ring
- Arca compatible



QS-62 V3

- 1/4" camera screw & pin with D-ring
- Arca compatible



QS-60 V2

- 1/4" camera screw & pin with
- Arca compatible



QS-52



• For camera & spotting scopes w/1/4" screw & pin



QS-36

• 1/4" camera screw & pin




QS-29

- Anti-slip rubber pad
- 1/4" camera screw with D-ring

VEO MT-12



The newly designed Vanguard VEO MT-12 is the upgraded version of Vanguard's previous Multi-Mount 6. Ideal for mounting up to 4 pieces of gear, it features sturdy aluminum alloy material, is 25.6in/650mm long, has a large center locking ring, two safety pins, length adjustment bar and comes with two VEO+MA1s. Well thought out and built, if you are looking to mount multiple pieces of gear on a tripod look no further, the VEO MT-12 is your ideal solution







ENDEAVOR LDA

The Endeavor Lock Down LDA is manufactured for durability from solid stock of choice grade aluminum with a premium anodized finish to withstand the most adverse conditions and punishing use in rough terrain. Easy rotation and tilt equate to seamless and effortless target tracking when behind the firearm or crossbow. This is the perfect tripod accessory for the long distance or pro shooter.





SPECIFICATIONS

MODEL	SIZE(L x W x H)	WEIGHT	MATERIAL
ENDEAVOR LDA	67.2 x 72.9 x 34.9MM / 2.6 x 2.9 x I.4LN	165G/0.36LBS	ALUMINUM ALLOY

VEO+MAI







MODEL	FULL EXTENDED HEIGHT	WEIGHT	PAYLOAD	CENTER COLUMN PLATE DIAMETER	TUBE MATERIAL
VEO MTI2	650MM 25.6IN	1025G 2.26LBS	10KG 22.04LBS	58MM 2.28IN	ALUMINUM ALLOY

SHOOTING SUPPORTS

Optic Guard/Optic Guard Camo

BINOCULAR HARNESS

- Evenly distributes binocular weight for extended use
- Adjustable harness and binocular straps allow you to customize the fit for your shape and your binocular







BA-185 BINOCULAR ACCESSORY

• The BA-185 Binocular Tripod Adapter steadies a binocular for clear, relaxed, hands-free viewing. It works with any roof prism binocular that has a standard 1/4-20 thread tripod socket, and on most models its thin bridge will still allow you to set your binocular to the minimum interpupillary distance adiustment



VEO PA-10 SMARTPHONE HOLDER + BLUETOOTH

- Can hold up to 6.3 Inch Smart Phones
- Stand alone support
- 1/4" 20 Thread bolt capability
- Bluetooth Capable with IOS and Android



50MM SUNSHADE RIFLESCOPE ACCESSORY

- Fits on RS IV 4-16X50 and RS IV 5-20X50 Models
- Reduces Glare From Sun
- Reduces Glint Off Objective Lens
- Allows for Better Shooting in Bright Daylight Conditions
- Improves Target Visibility and protects lens
- Length: 2.5 Inches / 63.8 MM



SPEED MAG LEVER RIFLESCOPE ACCESSORY

- Easy-Mount Hinge Design
- Premium Style
- Easy Attachment to Vanguard Magnification Ring
- Ideal for 1-4x24 / 1-6x24 / 1-7x44 Models
- Finish: Hard Anodized
- Color: Black
- Material: Al6061 Aluminum

30 MM RS RINGS

RIFLESCOPE ACCESSORY

- Designed for Appeal, Strength, and Minimal Weight
- 30MM Premium Style
- Slotted Hex Nut Fastener With End Stop (For Securing to Base)
- 4 Hex Screws for Added Strength & Security
- Hard & Durable Finish
- Color: Black
- Attachment / Mount Type: Picatinny & Weaver
- Size: Low, Medium, High
- Material: Solid Bar



SPECIFICATIONS

	MODEL	HEIGHT	WIDTH	RING SIZE A	RING SIZE B	WEIGHT
	RS RINGS 30MM LOW WEAVER	1.89 IN. / 48.0MM	2.03 IN. / 51.5MM	0.885 / 22.48	1.06 IN. / 26.98MM	4.340Z / 123G
	RS RINGS 30MM MED WEAVER	2.0 IN. / 50.9MM	2.03 IN. / 51.5MM	1.0 / 25.4	1.18 IN. / 29.9MM	4.480Z / 127G
	RS RINGS 30MM HIGH WEAVER	2.13 IN. / 54.IMM	2.03 IN. / 51.5MM	1.125 / 28.58	1.3 IN. / 33.08MM	4.900Z / 139G
	RS RINGS 30MM LOW PICATINNY	1.89 IN. / 48.0MM	2.03 IN. / 51.5MM	0.885 / 22.48	1.06 IN. / 26.98MM	4.340Z / 123G
	RS RINGS 30MM MED PICATINNY	2.0 IN. / 50.9MM	2.03 IN. / 51.5MM	1.0 / 25.4	1.18 IN. / 29.9MM	4.40Z / 127G
	RS RINGS 30MM HIGH PICATINNY	2.13 IN. / 54.IMM	2.03 IN. / 51.5MM	1.125 / 28.58	1.3 IN. / 33.08MM	4.90Z / 139G

SUPREME

Virtually indestructible, the rugged Vanguard Supreme Series hard cases have innovative features for unmatched strength and durability. They are O-ring sealed, waterproof (up to a depth of 16.5 feet/5 meters), airtight, and built to withstand the most extreme conditions. Supreme cases are great for airline travel with an automatic pressure equalization valve. Anti-slip rubber feet and a solid carrying handle offer extra durability. Rest assured, your optics will be safe from all harm in these cases.







51 2011 10/1/10110				
MODEL	OUTSIDE DIMENSIONS	INSIDE DIMENSIONS	WEIGHT	
SUPREME 53F	24.8 X 20.4 X 9.4 IN 630 X 520 X 240 MM	22 X 17.7 X 7.8 IN 560 X 450 X 200 MM	23 LBS 10.4 KG	
SUPREME 46F	20.2 X 17.1 X 8.6 IN 515 X 435 X 220 MM	18.9 X 14.5 X 7.8 IN 480 X 370 X 200 MM	15 LBS 6.8 KG	
SUPREME 40F	18.3 X 14.3 X 7.6 IN 465 X 365 X 195 MM	16.9 X II.6 X 6.8 IN 430 X 295 X 175 MM	9.7 LBS 4.4 KG	
SUPREME 37F	16.3 X 9.2 X 7.6 IN 415 X 235 X 195 MM	16.3 X 10.2 X 6.8 IN 380 X 260 X 175 MM	8.6 LBS 3.9 KG	
SUPREME 27F	II X 9 8 X 6 6 IN 280 X 250 X 170 MM	II X 9 8 X 6 6 IN 250 X I90 X I50 MM	411BS 19 KG	

SHOOTING SUPPORTS

RETICLES

ENDEAVOR SLINGS

101B/101C/150G

- Shoulder pad is durable yet flexible to reduce shoulder pressure
- Anti-Slip Material for better carrying experience
- Thumb loop for easy transport
- Quick Adjustable ladder lock buckle to sling length up to 45.25 inches
- "W type" heavy duty reinforced sewn ends
- Rust Resistant Quick Detach/Attach Swivel hardware included

301B

- High Density Rubber Armored Strap
- Durable, Lightweight, Anti-Slip, Anti-Scratch and All Weather
- Thumb loop for easy transport

101B

- Quick Adjustable ladder lock buckle to sling length up to
- "Z" style construction allows for maximum grip and flexibility
- Could work properly as low -40° F to as high 185° F
- Rust Resistant Quick Detach/Attach Swivel hardware included

201B/201G/203B/203C

- 3"+ Wide Shoulder Pad provides all-day comfort
- Shoulder pad is durable yet flexible to reduce shoulder pressure
- Anti-Slip Texture and Thicker Pad for better carrying experience
- Thumb loop for easy transport

ENDEAVOR SLINGS

- Quick Adjustable ladder lock buckle to sling length
- 203B/203C Pockets for Mini-Tool Knife, Mini-Flash Light and Other Accessories
- Rust Resistant Quick Detach/Attach Swivel hardware included

203C

301B

203B

101C 150G 201B 201G

SPORTING OPTICS KEY FEATURES

HOYA GLASS

PREMIUM HOYA ED GLASS

Setting new standards with a rating of more than 95% light transmission, HOYA ED glass launches Vanguard optical design above the competition, ensuring brightness and clarity even in the lowest light.



SK-15 PRISMS

Exceeding BAK4 prisms in image quality, SK15 minimizes undesirable internal reflections and light rays resulting in increased edge-to-edge brightness and clarity.



PREMIUM ED GLASS

Vanguard's Extra-low Dispersion (ED) glass significantly reduces chromatic aberrations, allowing clear, sharp viewing with high contrast.



MULTIGUARD® COATINGS

Vanguard's MultiGuard® coatings provide multiple layers of antireflective compounds resulting in optimal light transmission and producing a remarkably clear field of view.



TRIPOD MOUNTABLE

With the tripod mountable feature, you can easily mount your optics to any tripod or monopod for hands-free stable viewing.



RAPID FOCUS EYEPIECE

The rapid focus eyepiece can be adjusted in seconds, giving you a clear and crisp view of your target.



WATERPROOF & FOGPROOF

Vanguard's O-ring seals completely prevent moisture, dust, and debris from entering the optics. Nitrogen purging prevents fogging in extreme weather conditions.



LOCKING DIOPTER RING

The diopter lets users adjust the focus to accommodate differences between each of their eyes. The diopter rings lock so that adjustments don't need to be made before each use.



2 & 3 STAGE TWIST EYE CUPS

Vanguard's twist-up eye cups come in 2 or 3 stage adjustments, allowing a customized fit for a comfortable viewing experience with or without eyeglasses.



LOW LIGHT PERFORMANCE

The fully multicoated lenses improve light transmission for bright and clear images, with greater low-light



WINDAGE & ELEVATION RESET

Easily reset your windage and elevation adjustments back to zero by rotating each dial to their original factory setting.



EASY PARALLAX ADJUSTMENT

The easy parallax adjustment dial allows you to adjust to the optimum focus for every target distance, thus preventing aiming errors due to parallax.

TRIPODS


SHOOTING SUPPORTS HEADS & ACCESSORIES


NEW PRODUCTS



DUPLEX


A popular reticle design that is uncluttered and designed for a wide variety of applications. Four defined and thicker posts draw the eye to center and give way to a central fine crosshair. The allround reticle perfect for hunting in thick brush, for fast target acquisition or for big game where precision is also needed.






GERMAN 4 ILLUMINATED

Three contrasting and bold outer lines allow the shooter to quickly bracket the target and guide the eye to the center even in challenging lighting conditions or against busy outdoor backgrounds. The fine center lines still allow for precise shot placement at extended ranges while the open upper quadrants provide a clear and unobstructed sight picture which is especially helpful on moving targets or game.






All Vanguard Dispatch™ reticles are designed by lifelong shooters and optical engineers to deliver fast target holdover in an uncomplicated, user-friendly system. The Dispatch™ ballistic calculator computes external input data like caliber, bullet weight, velocity, ballistic coefficient, elevation, temperature, humidity etc. to generate and display the OPS and the actual bullet drop at each distance. All variables are combined to give the shooter the best possible result in speed and accuracy. Dispatch™ reticles can be used in conjunction with almost any factory or hand load combination. Factory ammo will be continually updated as new loads are introduced from the various ammunition manufacturers.



- Standard Hunting Calibers
- Smooth transition from zero to 600 yards
- Caliber class examples: .243 Win, .270 Win, .308 Win, .30-06 Spring



- High Velocity Varmint
- Ultimate close-to-long-distance reticle
- Crisp and clean .125 inches for fine shot placement on small targets
- Caliber class examples: .204 Ruger, .22-250 Rem, .220 Swift



- Magnum Calibers
- Smooth transition from zero to 800 yards
- Caliber class examples: .270 WSM, .300 Win, .300 Wby, .338 RUM



- MSR Tactical / CQB
- For tactical speed and precision
- Encompassing CQB and longer distance
- Caliber class examples: 5.56 NATO, .223 Rem



\lesssim	MODEL	RET	ICLE	FIELD OF VIE	W	TUBE	EYE RELIE	F WEIGH	IT LENGTI
SPECIFICATIONS	ENDEAVOR RS IV I-4X24 G	GERN	MAN 4	II6.4 - 27.1 FT /IOO YDS 38.8	- 9 M /IOO M	30 MM	105 - 92 MN	1 17.6 OZ 50	18G II IN 28I N
Ħ	ENDEAVOR RS IV 1.5-6X42 G	GERN	MAN 4	70.5 - I5.6 FT /IOO YDS 23.5	- 5.2 M /IOO M	30 MM	104.5 - 90 M	M 22.2 0Z 63	30 G II.9 IN 303
힏	ENDEAVOR RS IV 2-8X32 D	DUF	PLEX	49.6 - I3.I FT /I00 YDS I6.5	- 4.4 M /IOOM	30 MM	105 - 90 MN	1 17.60Z 50	
	ENDEAVOR RS IV 2.5-IOX50 G	GERN	MAN 4	44 - II FT / IOO YDS I5 - 4	1 M /IOOM	30 MM	102 - 92 MN	1 24 OZ 680	0 G 14 IN 355 I
욷	ENDEAVOR RS IV 2.5-IOX50 DS6	DISPAT	TCH 600	44 - II FT / IOO YDS I5 - 4		30 MM	102 - 92 MN	_	
တ	ENDEAVOR RS IV 3-12X56 G	GERN	MAN 4	37.5 - 9.1 FT /100 YDS 12.5	- 43M /IOOM	30 MM	105 - 90 MN	1 25 OZ 720	D G 14.1 IN 358
	ENDEAVOR RS IV 4-16X44 D	DUF	PLEX	27.I - 6.5 FT /IOO YDS 9 - 2	2.2 M /IOOM	30 MM	102 - 90 MN	1 24 OZ 670	D G 13.2 IN 336
	ENDEAVOR RS IV 4-16X44 DS6	DISPAT	TCH 600	27.I - 6.5 FT /IOO YDS 9 - 2	2.2 M /IOOM	30 MM	102 - 90 MN	1 24 OZ 670	D G 13.2 IN 336
	ENDEAVOR RS IV 4-16X44 DS8	DISPAT	ГСН 800	27.I - 6.5 FT /IOO YDS 9 - 2	2.2 M /IOOM	30 MM	102 - 90 MN	1 24 OZ 670	D G 13.2 IN 336
	ENDEAVOR RS IV 4-16X50 D	DUF	PLEX	26.I - 6.9 FT /IOO YDS 8.7 -	2.3 M /IOOM	30 MM	104 - 90MN	1 24 OZ 740	OG 14.5 IN 368
	ENDEAVOR RS IV 4-16X50 DS6	DISPAT	TCH 600	26.I - 6.9 FT /IOO YDS 8.7 -	2.3 M /IOOM	30 MM	104 - 90 MN	1 24 OZ 740	OG 14.5 IN 368
	ENDEAVOR RS IV 4-16X50 DS8	DISPAT	TCH 800	26.I - 6.9 FT /IOO YDS 8.7 -	2.3 M /IOOM	30 MM	104- 90 MN	1 24 OZ 740	OG 14.5 IN 368
	ENDEAVOR RS IV 5-20X50 D	DUF	PLEX	21.9 - 5.6 FT /100 YDS 7.3 - 1.9M /100M		30 MM	105 - 90 MN	1 25.7 OZ 73	80 G 14.8 IN 375
	ENDEAVOR RS IV 5-20X50 DSV	DISPATCH	H VARMINT	21.9 - 5.6 FT /100 YDS 7.3 -	1.9M /100M	30 MM	105 - 90 MN	1 25.7 OZ 73	80 G 14.8 IN 375
	ENDEAVOR RS VI 1642 G	GERN	MAN 4	II64 -17.75FT /100 YDS 38.8-5.92 M /100 M		30MM	105 - 90 MN	1 18.8 OZ 53	35G II IN 281 N
	ENDEAVOR RS VI 1624DS556	DISPATO	H TAC556	II6.4 -I7.75FT /IOO YDS 38.8-	5.92 M /IOO M	30MM	105 - 90 MN	1 18.8 OZ 53	35G II IN 281 N
ľ	ENDEAVOR RS VII 1744 G		MAN 4	91.35-12.27FT /100 YDS 30.45		30MM	96-88 MM		
	ENDEAVOR RS VII 1744 DS556	DISPATC	H TAC556	91.35-12.27FT /100 YDS 30.45-4.09M /100 M		30MM	96-88 MM		
<u>~</u> [MODEL	SI	ZE	FIELD OF VIEW		NEAR FOCU	JS E	YE RELIEF	WEIGHT
SPOTTIN	ENDEAVOR HD 65A		5 X 65	144-68 FT /I,000 YDS 48-23 N		14.8-18 FT 4.5-5		19-20 MM	51 OZ 1.45 KG
∃h	ENDEAVOR HD 82A	20-6	0 X 82	IIO-52 FT /I,000 YDS 37-17 M	19.7-21.3 FT 6-6.	5 M	19-20 MM	67 OZ 1.89 KG	
ड	VEO HD 80A		O X 80	IIO-52 FT / IOOO YDS 37-I7 M		19.7-21.3 FT 6-6		19-20MM	49.4 OZ 1400 G
S	VEO HD 60A	15~45	5 X 60	14I-68 FT / 1000 YDS 47-23 M		16.4-19.7 FT 5-6		19-20M M	38.8 OZ 1100 G
SCOPE	VESTA 350A	12~45	5 X 50	157~52 FT /I,000 YDS 52~17 N		29.5~39.4 FT 9~	12 M	II MM	21.2 OZ 600 G
띪	VESTA 350S	12~45	5 X 50	157~52 FT /I,000 YDS 52~17 N	1/I,000 M	29.5~39.4 FT 9~	12 M	II MM	21.1 OZ 598 G
	VESTA 460A	15~50	0 X 60	125~57 FT /1,000 YDS 42~19 N	32.8~39.4 FT 10~	32.8~39.4 FT 10~12 M II M		21.5 OZ 609 G	
	VESTA 560A	15~45	5 X 60	104~63 FT /I,000 YDS 35~21 N	1,000 M	26.3~29.5FT 8~	9 M	16~21 MM	45.7 OZ 1293 G
۵	MODEL	SI	ZE	FIELD OF VIEW	1	NEAR FOCUS	EYE RELIEF	ADJUST. PUPILI	LARY WEIGH
7	VEO HD2 8420	8)	X 42	377 FT /I,000 YDS I26 M /I,00	0 M	6.6 FT 2.0 M	19 MM	58-74 MM	25 OZ 710
	VEO HD2 1042	10)	X 42	340 FT /I,000 YDS II4 M /I,00	0 M	6.6 FT 2.0 M	18 MM	58-74 MM	25 OZ 710
BINOCULAR/MON	VEO HD 8420	8)	X 42	372 FT /I,000 YDS 124 M /I,000 M		6.6 FT 2.0 M	19 MM	58-74 MM	26.8 OZ 76
Æ١	VEO HD 1042	10)	X 42	342 FT /I,000 YDS II4 M /I,00	0 M	6.6 FT 2.0 M	18 MM	58-74 MM	27.I OZ 76
\leq	VEO ED 8420	8)	X 42	330 FT / 1000 YDS 110 M / 1 00	10 M	8.2 FT 2.5 M	19 MM	55-75MM	22.58 OZ 64
일[VEO ED 1042	10)	X 42	314 FT / 1000 YDS 105 M / 1 00	10 M	9.2 FT 2.8 M	16 MM	55-75MM	22.58 OZ 64
	VEO ED 1050	10)	X 50	282 FT / 1000 YDS 94 M / 100	10 M	9.8 FT 3.0 M	19 MM	59.5-75MM	27.58 OZ 78
CULARS	VESTA 8250	8 X	X 25	340 FT /I,000 YDS II4 M /I,00	0 M	8.2 FT 2.5 M	12.5 MM	56-74 MM	8.5 OZ 24
æ[VECTA CACC	ΩV	X 42	325 FT /I,000 YDS 108 M /I,000 M		6.9 FT 2.1 M	19 MM	E0 74 MM	22.22 OZ 63
	VESTA 8420	0 /		0201171,000 120 1001171,00			IVIIVI GI	56-74 MM	
S	VESTA 842U VESTA 1025		X 25	330 FT /I,000 YDS IIO M /I,00	0 M	8.2 FT 2.5 M	IO MM	56-74 MM 56-74 MM	8.32 OZ 23
S		10)							
S	VESTA 1025 VESTA 1042 VESTA 1042RT	10) 10)	X 42 X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 298 FT /I,000 YDS I00 M /I,00	10 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M	10 MM 17 MM 17 MM	56-74 MM	8.32 OZ 23 22.01 OZ 62 22.01 OZ 62
S	VESTA 1025 VESTA 1042 VESTA 1042RT VEO HD 2 1042M	(0) (0) (0) (0)	X 42 X 42 X42	330 FT /I,000 YDS IIO M /I,00 298 FT /I,000 YDS IOO M /I,00 298 FT /I,000 YDS IOO M /I,00 342 FT /I,000 YDS II4 M /I,00	0 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M	10 MM 17 MM 17 MM 18 MM	56-74 MM 56-74 MM	8.32 OZ 23 22.01 OZ 62 22.01 OZ 62 11.5 OZ 328
S	VESTA 1025 VESTA 1042 VESTA 1042RT	(0) (0) (0) (0)	X 42 X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 298 FT /I,000 YDS I00 M /I,00	0 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M	10 MM 17 MM 17 MM	56-74 MM 56-74 MM 56-74 MM	8.32 OZ 23 22.01 OZ 62 22.01 OZ 62
	VESTA 1025 VESTA 1042 VESTA 1042RT VEO HD 2 1042M	(0) (0) (0) (0) (0)	X 42 X 42 X42	330 FT /I,000 YDS IIO M /I,00 298 FT /I,000 YDS IOO M /I,00 298 FT /I,000 YDS IOO M /I,00 342 FT /I,000 YDS II4 M /I,00	0 M 0 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM - - -	8.32 OZ 23 22.01 OZ 62 22.01 OZ 62 11.5 OZ 328
	VESTA 1025 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS IIO M /I,00 298 FT /I,000 YDS IOO M /I,00 298 FT /I,000 YDS IOO M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS I3I M /I,00	0 M 0 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM - -	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25
S HEADS	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-I23V	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS IIO M /I,00 298 FT /I,000 YDS IIO M /I,00 298 FT /I,000 YDS IOO M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 IM /I,00 FRONTAL TII -45°~90° -60°~90°	0 M 10 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM - - -	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 324 8.820Z 25 WEIGHT 1.45 LBS 658 6 2.18 LBS 990 6
	VESTA 1025 VESTA 1042 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VEO2 PH-26	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°~90° -60°~90° -90° TO +60°	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM - - - MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G
	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-I23V	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS I00 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°-90° -60°~90° -90° T0 +60° -90° T0 +60°	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 145 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G
	VESTA 1025 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°~90° -60°~90° -90° TO +60°	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG
	VESTA 1025 VESTA 1042 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-BH50WM	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS I14 M /I,00 392 FT /I,000 YDS I31 M /I,00 FRONTAL TII -45°-90° -60°-70° T0 +60° -60° T0 +90° /	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 14 LBS 675 G	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 6 2.18 LBS 990 6 0.8 LBS 365 6 1.1 LBS 515 6 8.8 LBS 4 KG
	VESTA 1025 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM	(0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS I00 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°-90° -60°~90° -90° T0 +60° -90° T0 +60°	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG
HEADS 30	VESTA 1025 VESTA 1042 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-BH50WM PH 304	10 3 10 3 10 3 8 3 QL	X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS I31 M /I,00 FRONTAL TII -45°~90° -60°~90° -90° T0 +60° -60° T0 +90° / 0° T0 +90°	0 M 0 M 0 M 0 M 0 M 0 M 0 M 0 M 0 M 0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 1.4 LBS 675 G 1.6 LBS 730 G	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 6 2.18 LBS 990 6 0.8 LBS 365 6 1.1 LBS 515 6 8.8 LBS 4 KG 11.0 LBS 5 KG 8.8 LBS 4 KG
HEADS 30	VESTA 1025 VESTA 1042 VESTA 1042 VESTA 1042RT VEO HD 2 1042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-BH50WM PH 304 MODEL RS RINGS 30MM LOW WEAVER	10 % 10 % 10 % 10 % 10 % 10 % 10 % 10 %	X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 342 FT /I,000 YDS II4 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°~90° -60°~90° -90° T0 +60° -60° T0 +90° / 0° T0 +90° WIDTI 4 2.03 IN. / 51	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360° 360° 360° 360° 360° 360° 360° 360°	10 MM 17 MM 17 MM 18 MM 17.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 1.4 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 6 2.16 LBS 990 6 0.8 LBS 365 6 1.1 LBS 515 6 8.8 LBS 4 KG 11.0 LBS 5 KG 8.8 LBS 4 KG
HEADS 30 MM	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-114V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-PH28WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM MED WEAVER	(0) (0) (0) (0) (0) (0) (0) (0)	X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 392 FT /I,000 YDS II0 M /I,00 392 FT /I,000 YDS II1 M /I,00 392 FT /I,000 YDS II1 M /I,00 FRONTAL TII -45°~90° -60°~90° -90° T0 +60° -90° T0 +60° / 0° T0 +90° WIDTI 4 2.03 IN. / 51	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360° 360° 360° 360° 10.885 / 2 1.0 / 25	10 MM 17 MM 18 MM 17.7 MM 18.7 MM	56-74 MM 56-74 MM 56-74 MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 145 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG 11.0 LBS 5 KG 8.8 LBS 4 KG
HEADS 30 MM RS	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I4V ALTA PH-I23V VE02 PH-26 VE02 PH-28 VE02-PH-28WM VE02-PH28WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM MED WEAVER RS RINGS 30MM HIGH WEAVER	(0) (0) (10) (10) (10) (10) (10) (10) (1	X 42	330 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS II0 M /I,00 298 FT /I,000 YDS I00 M /I,00 392 FT /I,000 YDS II0 M /I,00 392 FT /I,000 YDS II1 M /I,00 392 FT /I,000 YDS II3 M /I,00 FRONTAL TII -45°-90° -60°-90° -90° T0 +60° -90° T0 +60° / 0° T0 +90° WIDTI 4 2.03 IN. / 51 1 2.03 IN. / 51	0 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360° 360° 360° 10.885 / 2 1.0 / 25 1.125 / 28	10 MM 17 MM 18 MM 17.7 MM 18.7.7 MM	56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 1.4 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM 1.18 IN. / 29.9MM 1.3 IN. / 33.08MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 21.02 62 22.01 0Z 62 22.01 0Z 62 22.01 0Z 62 8.820Z 25 WEIGHT 145 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG II.0 LBS 5 KG 8.8 LBS 4 KG WEIGHT 4.340Z / 1236 4.480Z / 1236 4.900Z / 139G
HEADS 30 MM RS	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-I23V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-PH28WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM HIGH WEAVER RS RINGS 30MM LOW PICATINN	10 3 10 3 10 3 10 3 10 3 10 3 10 3 10 3	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II3 M /I,000 392 FT /I,000 YDS II3 M /I,000 FRONTAL TII -45°~90° -60°~90° -90° T0 +60° -90° T0 +60° / 0° T0 +90° WIDTI 4 2.03 IN. / 51 4 2.03 IN. / 51 4 2.03 IN. / 51	10 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360° 360° 360° 100°	10 MM 17 MM 18 MM 17.7 MM 18.7.7 MM 17.7 MM 10.7.7 MM 10.7 MM 10	56-74 MM 56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 14 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM 1.3 IN. / 33.08MM 1.06 IN. / 26.99MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 21.02 62 22.01 0Z 62 22.01 0Z 62 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 5 KG 8.8 LBS 4 KG WEIGHT 4.340Z / 123G 4.900Z / 139G 4.340Z / 123G
HEADS 30 MM RS	VESTA I025 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-BH50WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM HIGH WEAVER RS RINGS 30MM LOW PICATINN RS RINGS 30MM MED PICATINN	10 3 10 3 10 3 10 3 10 3 10 3 10 3 10 3	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II1 M /I,000	10 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 8.2 FT 2.5 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360° 10.2 S 1.0 / 25 1.125 / 26 1.0 / 25	10 MM 17 MM 18 MM 177 MM 18 77 MM 177 MM 18 MM 175	56-74 MM 56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 14 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM 1.18 IN. / 29.9MM 1.18 IN. / 29.9MM 1.18 IN. / 29.9MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG 11.0 LBS 5 KG 8.8 LBS 4 KG 11.0 LBS 5 KG 4.340Z / 123G 4.480Z / 127G 4.900Z / 133G 4.40Z / 127G
HEADS 30 MM	VESTA I025 VESTA I042 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-I23V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-PH28WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM HIGH WEAVER RS RINGS 30MM LOW PICATINN	10 3 10 3 10 3 10 3 10 3 10 3 10 3 10 3	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II0 M /I,000 392 FT /I,000 YDS II1 M /I,000	10 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATIO 360° 360° 360° 360° 360° 360° 100°	10 MM 17 MM 18 MM 177 MM 18 77 MM 177 MM 18 MM 175	56-74 MM 56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 14 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM 1.3 IN. / 33.08MM 1.06 IN. / 26.99MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 21.02 62 22.01 0Z 62 22.01 0Z 62 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 990 G 0.8 LBS 365 G 1.1 LBS 5 KG 8.8 LBS 4 KG WEIGHT 4.340Z / 123G 4.900Z / 139G 4.340Z / 123G
HEADS 30 MM RS	VESTA I025 VESTA I042 VESTA I042RT VEO HD 2 I042M VESTA 8320M MODEL ALTA PH-I14V ALTA PH-123V VE02 PH-26 VE02 PH-28 VE02-PH28WM VE02-BH50WM PH 304 MODEL RS RINGS 30MM LOW WEAVER RS RINGS 30MM HIGH WEAVER RS RINGS 30MM LOW PICATINN RS RINGS 30MM MED PICATINN	10 3 10 10 10 10 10 10 10 10 10 10 10 10 10	X 42	330 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 298 FT /I,000 YDS II0 M /I,000 342 FT /I,000 YDS II0 M /I,000 342 FT /I,000 YDS II1 M /I,000 392 FT /I,000 YDS II1 M /I,000	10 M	8.2 FT 2.5 M 6.9 FT 2.1 M 6.9 FT 2.1 M 6.5 FT 2.0 M 8.2 FT 2.5 M ROTATION 360° 360° 360° 360° 360° 360° 360° 10 / 25 1.0 / 25 1.0 / 25 1.125 / 28 2.2 DAD CENT	10 MM 17 MM 18 MM 177 MM 18 77 MM 177 MM 18 MM 175	56-74 MM 56-74 MM 56-74 MM 56-74 MM MAX LOAD 17.6 LBS 8 KG 13.2 LBS 6 KG 6.6 LBS 3.0 KG 11.0 LBS 5.0 KG 1.5 LBS 711 G 14 LBS 675 G 1.6 LBS 730 G RING SIZE B 1.06 IN. / 26.98MM 1.18 IN. / 29.9MM 1.3 IN. / 33.08MM 1.18 IN. / 29.9MM 1.3 IN. / 33.08MM	8.32 0Z 23 22.01 0Z 62 22.01 0Z 62 11.5 0Z 323 8.820Z 25 WEIGHT 1.45 LBS 658 G 2.18 LBS 365 G 1.1 LBS 515 G 8.8 LBS 4 KG 11.0 LBS 5 KG 8.8 LBS 4 KG 11.0 LBS 5 KG 4.340Z / 123G 4.480Z / 127G 4.900Z / 133G 4.40Z / 127G

MODEL

PORTA-AIM

WEIGHT MATERIAL

ALUMINUM ALLOY

LENGTH

12.2 IN | 310 MM

WIDTH

5.7 IN | 145 MM

HEIGHT

8.8-12.6 IN | 225-320 MM

WEIGHT

1.7 LBS | 798 G

SIZE(L X W X H)

ENDEAVOR LDA 67.2 X 72.9 X 34.9MM / 2.6 X 2.9 X 1.4LN 165G/0.36LBS

MODEL

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	STANDARD HEIGHT	LEG DIAMETER	MATERIAL	LEG SECTIONS	HEAD	MAX LOAD	WEIGHT
VEO 3T 204ABP	15.9 IN 405 MM	55.I IN 1400 MM	40.9 IN 1040 MM	20	ALUMINUM	4	VEO BP-45T	8.8 LBS 4 KG	3.28 LBS 1490 G
VEO 3T 204CBP	15.9 IN 405 MM	55.I IN 1400 MM	40.9 IN 1040 MM	20	CARBON FIBER	4	VEO BP-45T	8.8 LBS 4 KG	3.03 LBS 1375 G
VEO 3T 235ABP	16.1 IN 410 MM	61 IN 1550 MM	45.5 IN 1155 MM	23	ALUMINUM	5	VEO BP-50T	17.6 LBS 8 KG	3.85 LBS 1745 G
VEO 3T 235CBP	16.1 IN 410 MM	61 IN 1550 MM	45.5 IN 1155 MM	23	CARBON FIBER	5	VEO BP-50T	17.6 LBS 8 KG	3.53 LBS 1600 G
VEO 3T 265HABP	17.3 IN 439 MM	65.4 IN 1660 MM	50.2 IN 1275 MM	26	ALUMINUM	5	VEO BP-I20T	26.5 LBS 12 KG	4.66 LBS 2115 G
VEO 3T 265HCBP	17.3 IN 439 MM	65.4 IN 1660 MM	50.2 IN 1275 MM	26	CARBON FIBER	5	VEO BP-I20T	26.5 LBS 12 KG	4.21 LBS 1910 G
VE03T 235AP	16.1 IN 410 MM	60.8 IN 1545 MM	45.I IN II45 MM	23	ALUMINUM	5	VEO PH-20T	13.2 LBS 6 KG	3.74 LBS 1695 G
VE03T 235CP	16.1 IN 410 MM	60.8 IN 1545 MM	45.I IN II45 MM	23	CARBON FIBER	5	VEO PH-20T	13.2 LBS 6 KG	3.74 LBS 1695 G
VEO 3 263AB	29.1 IN 738 MM	70.67 IN 1795 MM	57.7 IN 1465 MM	26MM	ALUMINUM	3	VEO BH-160S	33.06 LBS 15 KG	4.72 LBS 2142 G
VEO 3 263CB	29.1 IN 738 MM	70.67 IN 1795 MM	57.7 IN 1465 MM	26MM	CARBON FIBER	3	VEO BH-160S	33.06 LBS 15 KG	4.19 LBS 1900 G
ALTA PRO 2 264AO	27.8 IN 705 MM	63.9 IN 1622 MM	50.6 IN 1285 MM	26 MM	ALUMINUM	4	ALTA PH-31	II LBS 5 KG	5.10 LBS 2315 G
ALTA PRO 2 263AV	26.9 IN 683 MM	67.6 IN 1717 MM	54.5 IN 1385 MM	26 MM	ALUMINUM	3	ALTA PH-II4V	15.4 LBS 7 KG	5.31 LBS 2410 G
ALTA PRO 2 263CV	26.9 IN 683 MM	67.6 IN 1717 MM	54.5 IN 1385 MM	26 MM	CARBON FIBER	3	ALTA PH-II4V	15.4 LBS 7 KG	4.85 LBS 2200 G
VEO2 PRO 203AO	22 IN 560 MM	57.5 IN 1460 MM	45.9 IN 1165 MM	20MM	ALUMINUM	3	VEO 2 PH-26	6.6 LBS 3 KG	3.14 LBS 1425 G
VEO2 PRO 233AO	22 IN 560 MM	57.5 IN 1460 MM	45.7 IN 1160 MM	23MM	ALUMINUM	3	VEO 2 PH-28	8.8 LBS 4 KG	3.71 LBS 1683 G
VEO2 PRO 233CO	22 IN 560 MM	575 IN 1460 MM	46.1 IN 1170 MM	23MM	CARBON FIBER	3	VEO 2 PH-28	8.8 LBS 4 KG	3.19 LBS 1446 G
VEO2 PRO 263AO	24 IN 610 MM	63 IN 1600 MM	50.8 IN 1290 MM	26MM	CARBON FIBER	3	VEO 2 PH-28	II LBS 5 KG	4.24 LBS 1926 G
VEO2 PRO 233AV	22.8 IN 580 MM	57.5 IN 1460 MM	46 .I IN II70 MM	23MM	ALUMINUM	3	VEO 2 PH-13	8.8 LBS 4 KG	3.77 LBS 1710 G
VEO2 PRO 233CV	22.8 IN 580 MM	57.5 IN 1460 MM	46.3 IN 1175 MM	23MM	CARBON FIBER	3	VEO 2 PH-13	8.8 LBS 4 KG	3.29 LBS 1494 G
VEO2 PRO 263AV	23.2 IN 590 MM	59 IN 1500 MM	47.3 IN 1200 MM	26MM	ALUMINUM	3	VEO 2 PH-15	II LBS 5 KG	4.64 LBS 2107 G
VEO2 PRO 263CV	22.8 IN 580 MM	57.5 IN 1460 MM	46.3 IN 1175 MM	26MM	CARBON FIBER	3	VEO 2 PH-15	II LBS 5 KG	4.00 LBS 1815 G
VEO 3GO 204AB	13.5 IN 345 MM	51.5 IN 1310 MM	39.7 IN 1010 MM	20MM	ALUMINUM	4	T-45	6.6 LBS 3 KG	2.08 LBS 945 G
VEO 3GO 204CB	13.5 IN 345MM	51.5 IN 1310 MM	39.7 IN 1010 MM	20MM	CARBON FIBER	4	T-45	6.6 LBS 3 KG	1.79 LBS 816 G
VEO 3GO 235AB	12.9 IN 330 MM	53.5 IN 1360 MM	41.7 IN 1060 MM	23MM	ALUMINUM	5	T-50	8.8 LBS 4 KG	2.70 LBS 1225 G
VEO 3GO 235CB	12.9 IN 330 MM	53.5 IN 1360 MM	41.7 INI 1060 MM	23MM	CARBON FIBER	5	T-50	8.8 LBS 4 KG	2.34 LBS 1065 G
VEO 3GO 265HAB	16.1 IN 410 MM	65.5 IN 1665 MM	49.6 IN 1260 MM	26MM	ALUMINUM	5	ALTA BH-102	22.0 LBS 10 KG	3.65 LBS 1659 G
VEO 3GO 265HCB	16.1 IN 410 MM	65.5 IN 1665 MM	49.6 IN 1260 MM	26MM	CARBON FIBER	5	ALTA BH-102	22.0 LBS 10 KG	3.II LBS 1415 G
VEO 2 AM-234 TU	24.4 IN 620 MM	62.6IN 1590 MM	-	23 MM	ALUMINUM	-	-	-	1.95 LBS 885 G
VEO 2 CM-234 TU	24.4 IN 620MM	62.6 IN 1590 MM	-	23 MM	CARBON FIBER	-	- T 10	-	1.78 LBS 809 G
VESTA FB 204ABS	12.3 IN 315 MM	39.7 IN 1010 MM	35.4 IN 900 MM	20MM	ALUMINUM	4	T-46	6.6 LBS 3.0 KG	1.79 LBS 812 G
VESTA FB 204AB	14.7 IN 375 MM	5I.I IN I300 MM	44.I IN II20 MM	20MM	ALUMINUM	4	T-46	6.6 LBS 3.0 KG	2.00 LBS 906 G
VESTA FB 235AB	14.7 IN 375 MM	56.2 IN 1430 MM	50.2 IN 1275 MM	23MM	ALUMINUM	5	T-51	9.9 LBS 4.5 KG	2.58 LBS 1170 G
VESTA 203AP	22.5 IN 570 MM	61 IN 1550 MM	48 IN 1220 MM	20 MM	ALUMINUM	3	PH-23	7.7 LBS 3.5 KG	2.44 LBS 1105 G
VESTA 204AP	20.5 IN 520 MM	61 IN 1550 MM	49.4 IN 1255 MM	20 MM	ALUMINUM	4	PH-23	7.7 LBS 3.5 KG	2.49 LBS 1132 G
VESTA 233AP	22.91 IN 582 MM	61 IN 1550 MM	48.I IN I22I MM	23 MM	ALUMINUM	3	PH-23	7.7 LBS 3.5 KG	2.81 LBS 1275 G
VESTA 234AP	20.67 IN 525 MM	61 IN 1550 MM	50.5 IN 1282 MM	23 MM	ALUMINUM	4	PH-23	7.7 LBS 3.5 KG	2.89 LBS 1313 G
VESTA 203AGH	22.44 IN 570 MM	61 IN 1550 MM	48.2 IN 1255 MM	20 MM	ALUMINUM	3	GH-45	7.7 LBS 3.5 KG	2.47 LBS II20 G
VESTA 233AGH	22.95 IN 583 MM	61 IN 1550 MM	48.5 IN 1231 MM	23 MM	ALUMINUM	3	GH-45	7.7 LBS 3.5 KG	2.99 LBS 1360 G
ESPOD CX I	II.6 IN 295 MM	21.3 IN 540 MM	-	-	-	3	-	5.5 LBS 2.5 KG	1.47 LBS 665 G
ESPOD CX I OS	14.8 IN 375 MM	24.4 IN 620 MM	-	-	-	3	-	6.6 LBS 3.0 KG	2.1 LBS 934 G
VESTA TTI BP	6.89 IN 175 MM	3.94 IN 100 MM	-	-	-	-	-	4.4 LBS 2 KG	0.34 LBS 156 G
VS-82	10.0 IN 255 MM	9.25 IN 235 MM	-	-	-	-	-	5.5 LBS 2.5 KG	0.94 LBS 430G

TRIPODS

SUPREME

MODEL	FOLDED HEIGHT	EXTENDED HEIGHT	LEG DIAMETER	WEIGHT
EQUALIZER IQS	6.9 IN 176 MM	10 IN 255 MM	14 MM	0.7 LBS 320 G
EQUALIZER 2QS	II IN 277 MM	28 IN 715 MM	17 MM	1.0 LBS 453 G
EQUALIZER 2	12.7 IN 325 MM	27 IN 685 MM	17 MM	0.9 LBS 430 G
QUEST T62U	27.5 IN 700 MM	62 IN 1575 MM	20 MM	2.20 LBS 1000 G
QUEST M49	22 IN 560 MM	49 IN 1245 MM	20 MM	0.66 LBS 300 G
QUEST M62	26.3 IN 670 MM	62 IN 1575 MM	20 MM	0.77 LBS 350 G
QUEST B38	19.1 IN 485 MM	38 IN 965 MM	20 MM	1.14 LBS 520 G
QUEST B62	27.1 IN 690 MM	62 IN 1575 MM	20 MM	1.43 LBS 650 G
SCOUT M62	22.0 IN 560 MM	62 IN 1575 MM	20 MM	0.57 LBS 260 G
SCOUT B62	22.2 IN 565 MM	62 IN 1575 MM	20 MM	1.10 LBS 500 G

MODEL	OUTSIDE DIMENSIONS	INSIDE DIMENSIONS	WEIGHT	
SUPREME 53F	24.8 X 20.4 X 9.4 IN 630 X 520 X 240 MM	22 X 17.7 X 7.8 IN 560 X 450 X 200 MM	23 LBS 10.4 KG	
SUPREME 46F	20.2 X 17.1 X 8.6 IN 515 X 435 X 220 MM	18.9 X 14.5 X 7.8 IN 480 X 370 X 200 MM	15 LBS 6.8 KG	
SUPREME 40F	18.3 X 14.3 X 7.6 IN 465 X 365 X 195 MM	16.9 X II.6 X 6.8 IN 430 X 295 X 175 MM	9.7 LBS 4.4 KG	
SUPREME 37F	16.3 X 9.2 X 7.6 IN 415 X 235 X 195 MM	16.3 X 10.2 X 6.8 IN 380 X 260 X 175 MM	8.6 LBS 3.9 KG	
SUPREME 27F	II X 9.8 X 6.6 IN 280 X 250 X 170 MM	II X 9.8 X 6.6 IN 250 X 190 X 150 MM	4.1 LBS 1.9 KG	



9157 EAST M-36 WHITMORE LAKE,MI 48189

WWW.VANGUARDWORLD.COM